



## TECHNIQUES

TECHNOLOGIE HYBRID	
MOTEUR	SyncDrive Pro, 85Nm, powered by Yamaha
COMMANDE	RideControl GO integrated in TT, RideControl Ergo 3
ECRAN	Wireless display compatible
BATTERIE	EnergyPak Smart 800, EnergyPak Plus range extender compatible (exclude S Size)
CADRE	
TAILLES	S, M, L, XL
COLORIS	Cobalt/Black
CADRE	ALUXX SL-grade aluminum, Advanced Forged Composite Upper Rocker, 160mm Maestro suspension system, 'Boost' 148x12mm, Universal Derailleur Hanger
FOURCHE	RockShox Domain R 29er, 170mm travel, 15x110 Boost, Maxle Stealth, E-bike Approved
AMORTISSEUR	Fox Float DPS Performance, EVOL Large Volume sleeve, 3-position lever, 205x62.5mm Trunnion mount, custom tuned
COMPOSANTS	
CINTRE	Giant Contact Trail, 35x800mm
POIGNÉES	Giant Tactal Pro-E, single lock-on
POTENCE	Giant Contact SL 35
TIGE DE SELLE	Giant Contact Switch, dropper, 30,9mm (S:125/M:150/ L&XL:170)
SELLE	Giant Romero Trail
PÉDALES	Flat pedal
DÉRAILLEUR	
MANETTES	Shimano Deore
DÉRAILLEUR AVANT	MRP 1X HD2 custom co-molded chain guide
DÉRAILLEUR ARRIÈRE	Shimano Deore 12-speed
FREINS	Shimano Deore BR-M420, 4-piston, hydraulic disc, 203mm
LEVIER DE FREIN	Shimano Deore
CASSETTE	Shimano Deore CS-M6100-12, 10-51T, 12-speed
CHAÎNE	KMC e.12 Turbo, EcoProteq, e-bike optimized
PÉDALIER	Praxis Wavetm 36T Cold Forged 4130 premium steel Praxis e-Cadet+ custom forged crankarm set (S/M:160, L/XL:165)
BOITIER DE PÉDALIER	n/a

ROUES	
JANTES	Giant AM 29" [F] 27.5"[R], Tubeless ready, 30mm inner width
MOYEUX	Shimano MT410 Boost, Center-Lock, [F] 110x15 [R] 148x12mm Micro-Spline Drive Body Thru-axle
RAYONS	Sapim E-Lite [R] Race [F], e-bike optimized
PNEUS	Maxxis Minion DHF 29x2.6" foldable, Tubeless, EXO+, 3C MaxxTerra[F]Maxxis High Roller II 27.5x2.5" foldable, Tubeless, DoubleDown, 3C MaxxTerra Compound [R]
EXTRAS	Tubeless kit (liquid, valves, levers, manual, tool)
ACCESSOIRES	
ECLAIRAGE	Kit d'éclairage avant et arrière à piles
ANTI-VOL	Torx 25 Battery Lock with built-in Torque limiter
PORTE-BAGAGES	-
LIMITES	
POIDS TOTAL MAX AUTORISÉ	156 kg (vélo, cycliste et bagages)

Prix Public Conseillé: 5 500,00 €

## GÉOMÉTRIE

CADRE	S		M		L		XL	
	LOW	HIGH	LOW	HIGH	LOW	HIGH	LOW	HIGH
Longueur de tube de selle (mm)	400	425	450	475				
Angle de tube de selle	76,7°   77,5°	76,7°   77,5°	76,7°   77,5°	76,7°   77,5°				
Longueur du tube supérieur (mm)	569   568	595   594	622   621	649   648				
Longueur du tube de direction (mm)	100	100	110	120				
Angle du tube de direction	63,7°   64,5°	63,7°   64,5°	63,7°   64,5°	63,7°   64,5°				
Déport de fourche (mm)	44	44	44	44				
Trail (mm)	135,5   132,1	135   132	135   132	135,5   132,1				
Empattement (mm)	1209   1210	1236   1237	1265   1266	1295   1296				
Longueur des bases (mm)	457   455	454   454	454   454	454   454				
Drop du boîtier de pédalier (mm)	25   15	25   15	25   15	25   15				
Stack (mm)	636   632	635   632	645   641	654   650				
Reach (mm)	425   430	450   455	475   480	500   505				
Hauteur en statique (mm)	785   789	772   776	771   775	768   772				
Largeur de cintre (mm)	800	800	800	800				
Longueur de potence (mm)	40	40	50	50				
Longueur des manivelles (mm)	160	160	165	165				
Diamètre des roues	29" [F] 27.5" [R]		29" [F] 27.5" [R]		29" [F] 27.5" [R]		29" [F] 27.5" [R]	

Produits conformes aux exigences de sécurité (décret n° 2016-364 du 29 mars 2016). GIANT France se réserve le droit de modifier les spécifications sans préavis.