



TECHNIQUES

TECHNOLOGIE HYBRID	
MOTEUR	Giant SyncDrive Pro2 85Nm, PedalPlus 6-Sensor technology
COMMANDE	Giant RideControl Ergo3, grip integrated remote
ECRAN	Giant RideControl GO, frame integrated LED console Optional wireless ANT+ display
BATTERIE	Giant EnergyPak 800Wh, 22700 Lithium cell technology, Aluminium casing with highest safety standard (EN50604), CO2 Neutral production Giant EnergyPak Plus 250 range extender compatible (exclue S size)
CHARGEUR	Giant EnergyPak 6A smart charger, 60% in 2:15h
CONNECTIVITÉ	Giant RideControl App enabled ANT+ wireless display signal with e-bike profile
CADRE	
TAILLES	S, M, L, XL
COLORIS	Raw Aluminum / Black
CADRE	ALUXX SL-grade aluminum, Advanced Forged Composite Upper Rocker, 160mm Maestro suspension system, "Boost" 148x12mm, Universal Derailleur Hanger
FOURCHE	SR Suntour Durolox 38 Boost EQ, 170mm travel, 44mm offset, RC2, 15LH-110
AMORTISSEUR	Fox Float Performance, EVOL Large Volume sleeve, 2-position lever, 205x62.5mm Trunnion mount, custom tuned, recommended sag: 30%
COMPOSANTS	
CINTRE	Giant Contact Trail, 35x800mm
POIGNÉES	Giant Tactal Pro-E, tapered design, 135mm Ø28-30mm (S/M) 142mm Ø29-32mm (L/XL)
POTENCE	Giant Contact SL 35
TIGE DE SELLE	OBC Giant Contact Switch AT Travel adjustable 172D-CONTAC-0053 total length 315 T100-70MM / 172D-CONTAC-0052 total length 395 T140-110MM / 172D-CONTAC-0051 total length 470 T170-140MM / 172D-CONTAC-0050 total length 530 T200-170MM
SELLE	Giant Romero Trail
PÉDALES	Flatpedal
DÉRAILLEUR	
MANETTES	Shimano Cues LinkGlide
DÉRAILLEUR AVANT	MRP 1X HD2 custom co-molded chain guide
DÉRAILLEUR ARRIÈRE	Shimano Cues LinkGlide 11-speed
FREINS	Shimano BR-MT420, 4-piston, hydraulic disc, 203mm
LEVIER DE FREIN	Shimano Deore, I-spec EV
CASSETTE	Shimano Cues LinkGlide, CS-LG400-11, 11-50T, 11-speed
CHAÎNE	Shimano LinkGlide, CN-LG500
PÉDALIER	Praxis N.W. 36T Cold Forged 4130 premium steel Praxis e-HD forged crankarm set (S/M:160mm, L/XL:165mm)
BOITIER DE PÉDALIER	n/a

ROUES	
JANTES	Giant AM30, Tubeless ready, 30mm inner width, 29" [F] / 27.5" [R]
MOYEURS	Shimano MT410, Boost, Center-Lock, [F] 110x15 [R] 148x12mm HG Drive Body Thru-axle
RAYONS	Sapim E-Lite [R] Race [F], e-bike optimized
PNEUS	Maxxis Minion DHF 29x2.6" foldable, Tubeless, EXO+, 3C MaxxTerra [F] / Maxxis Assagai 27.5x2.5" WT foldable, Tubeless, DoubleDown, 3C MaxxGrip Compound [R] 1560-ASSEGA-0014
EXTRAS	Tubeless kit (liquid, valves, levers, manual, tool)
ACCESSOIRES	
ECLAIRAGE	Kit d'éclairage avant et arrière à piles
ANTI-VOL	Torx 25 Battery Lock with built-in Torque limiter
LIMITES	
POIDS TOTAL MAX AUTORISÉ	156 kg (vélo, cycliste et bagages)

Prix Public Conseillé: 5 500,00 €

GÉOMÉTRIE

CADRE	S		M		L		XL	
	LOW	HIGH	LOW	HIGH	LOW	HIGH	LOW	HIGH
Longueur de tube de selle (mm)	400	425	450	475				
Seat Post Insertion Depth (mm)	230	260	280	310				
Angle de tube de selle	76,7° 77,5°	76,7° 77,5°	76,7° 77,5°	76,7° 77,5°				
Longueur du tube supérieur (mm)	569 568	595 594	622 621	649 648				
Longueur du tube de direction (mm)	100	100	110	120				
Angle du tube de direction	63,7° 64,5°	63,7° 64,5°	63,7° 64,5°	63,7° 64,5°				
Déport de fourche (mm)	44	44	44	44				
Trail (mm)	135,5 132,1	135 132	135 132	135,5 132,1				
Empattement (mm)	1209 1210	1236 1237	1265 1266	1295 1296				
Longueur des bases (mm)	457 455	454 454	454 454	454 454				
Drop du boîtier de pédalier (mm)	25 15	25 15	25 15	25 15				
Stack (mm)	636 632	635 632	645 641	654 650				
Reach (mm)	425 430	450 455	475 480	500 505				
Hauteur en statique (mm)	785 789	772 776	771 775	768 772				
Largeur de cintre (mm)	800	800	800	800				
Longueur de potence (mm)	40	40	40	50				
Longueur des manivelles (mm)	160	160	165	165				
Diamètre des roues	29"	[F] 29" [R]	[F] 29" [R]	[F] 29" [R]				

Produits conformes aux exigences de sécurité (décret n° 2016-364 du 29 mars 2016). GIANT France se réserve le droit de modifier les spécifications sans préavis.