

REIGN E+ 3

GIANT



SPECS

Tecnologia Híbrida de Ciclismo	
MOTOR	Giant SyncDrive Pro2 85Nm, PedalPlus 6-Sensor technology
SENSOR	Giant RideControl Ergo3, grip integrated remote
ECRÃ	Giant RideControl GO, frame integrated LED console Optional wireless ANT+ display
BATERIA	Giant EnergyPak 800Wh, 22700 Lithium cell technology, Aluminium casing with highest safety standard (EN50604), CO2 Neutral production Giant EnergyPak Plus 250 range extender compatible (exculde S size)
CARREGADOR	Giant EnergyPak 6A smart charger, 60% in 2:15h
CONNECTIVITY	Giant RideControl App enabled ANT+ wireless display signal with e-bike profile
Quadro	
TAMANHOS	S, M, L, XL
CORES	Raw Aluminum / Black
QUADRO	ALUXX SL-grade aluminum, Advanced Forged Composite Upper Rocker, 160mm Maestro suspension system, 'Boost' 148x12mm, Universal Derailleur Hanger
FORQUILHA	SR Suntour DuroLux 38 Boost EQ, 170mm travel, 44mm offset, RC2, 15LH-110
AMORTECEDORES	Fox Float Performance, EVOL Large Volume sleeve, 2-position lever, 205x62.5mm Trunnion mount, custom tuned, recommended sag: 30%
Componentes	
GUIADOR	Giant Contact Trail, 35x800mm
PUNHOS	Giant Tactal Pro-E, tapered design, 135mm Ø28-30mm (S/M) 142mm Ø29-32mm (L/XL)
AVANÇO	Giant Contact SL 35
ESPIÃO DE SELIM	Giant Contact Switch, dropper, 30,9mm (S:125/M:150/L:170/XL:200)
SELIM	Giant Romero Trail
PEDAIS	Flatpedal
Transmissão	
MANETES	Shimano Cues LinkGlide
DESVIADOR DIANTEIRO	MRP 1X HD2 custom co-molded chain guide
DESVIADOR TRASEIRO	Shimano Cues LinkGlide 11-speed
TRAVÕES	Shimano BR-MT420, 4-piston, hydraulic disc, 203mm
MANÍPULOS DOS TRAVÕES	Shimano Deore, I-spec EV
CASSETTE	Shimano Cues LinkGlide, CS-LG400-11, 11-50T, 11-speed
CORRENTE	Shimano LinkGlide, CN-LG500
CONJUNTO PEDALEIRO	Praxis N.W. 36T Cold Forged 4130 premium steel Praxis e-HD forged crankarm set (S/M:160mm, L/XL:165mm)
MOVIMENTO CENTRAL	n/a

Rodas	
AROS	Giant AM30, Tubeless ready, 30mm inner width, 29" [F] / 27.5" [R]
CUBOS	Shimano MT410, Boost, Center-Lock, [F] 110x15 [R] 148x12mm HG Drive Body Thru-axle
RAIOS	Sapim E-Lite [R] Race [F], e-bike optimized
PNEUS	Maxxis Minion DHF 29x2.6" foldable, Tubeless, EXO+, 3C MaxxTerra[F] Maxxis High Roller II 27.5x2.5" foldable, Tubeless, DoubleDown, 3C MaxxTerra Compound [R]
EXTRAS	Tubeless kit (liquid, valves, levers, manual, tool)
Acessórios	
CADEADO	Torx 25 Battery Lock with built-in Torque limiter

Preço: 4 399,00 €

GEOMETRIA

Quadro	S	M	L	XL
	LOW HIGH	LOW HIGH	LOW HIGH	LOW HIGH
Comprimento do tubo do assento (mm)	400	425	450	475
Seat Post Insertion Depth (mm)	235	260	285	310
Ângulo do tubo do assento	76,7° 77,5°	76,7° 77,5°	76,7° 77,5°	76,7° 77,5°
Comprimento do tubo superior (mm)	569 568	595 594	622 621	649 648
Comprimento do tubo principal (mm)	100	100	110	120
Ângulo do tubo principal	63,7° 64,5°	63,7° 64,5°	63,7° 64,5°	63,7° 64,5°
Garfo ancinho (mm)	44	44	44	44
Trilha (mm)	135,5 132,1	135 132	135 132	135,5 132,1
distância entre eixos (mm)	1209 1210	1236 1237	1265 1266	1295 1296
Comprimento Chain Stay (mm)	457 455	454 454	454 454	454 454
Suporte inferior (mm)	25 15	25 15	25 15	25 15
Pilha (mm)	636 632	635 632	645 641	654 650
Alcançar (mm)	425 430	450 455	475 480	500 505
Altura do standover (mm)	785 789	772 776	771 775	768 772
Largura do guidão (mm)	800	800	800	800
Comprimento da haste (mm)	40	40	40	50
Comprimento da Manivela (mm)	160	160	165	165
Tamanho da roda	29"	[F] 29" [R]	[F] 29" [R]	[F] 29" [R]

Todas as especificações apresentadas estão sujeitas a alterações sem aviso prévio.