



SPECS

FRAME	
SIZES	S, M, L, XL
COLOURS	Gloss Obsidian Pulse/White
FRAME	ALUXX SL-Grade Aluminium front and rear triangles, Maestro Suspension, 160mm travel, 12x148mm thru-axle, integrated storage solution frame size S/XL: 29"F & 29"R commercial spec and 27.5" rear wheel compatible
FORK	NEW RockShox Zeb Delta RC damper 29"Boost 15x110 Maxle Stealth 170mm
SHOCK	RockShox SuperDeluxe, R, 205x62,5, custom tuned for Giant, recommended sag 30%
COMPONENTS	
HANDLEBAR	Giant Contact TR35, 800x35mm, 35mm rise,AL6061
GRIPS	Giant Tactal Pro, single, lock-on
STEM	Giant Contact SL 35, Diameter 35mm, 8 degree
SEATPOST	Contact Switch AT DSP with remote lever, 30,9mm
SADDLE	Giant Romero
PEDALS	Al body/AL cage Platform (GC,GT)
HEADSET	NO57
DRIVETRAIN	
SHIFTERS	NEW Shimano Deore SL M6200, 1x12
REAR DERAILLEUR	NEW Shimano Deore RD M7200, Shadow +
BRAKES	TRP EVO Comp, black HD-M7040 4 piston
BRAKE LEVERS	TRP EVO Comp
CASSETTE	NEW Shimano Deore, CS M6200 10x51
CHAIN	KMC X12
CRANKSET	Praxis Cadet HD M24 Boost, 32T, steel chainring, 55mm chainline with NEW MRP AMg CS Guide, Next generation upper guide
BOTTOM BRACKET	Shimano PressFit Praxis Pressfit

WHEELS	
RIMS	Giant TRA 2, F29"-R27.5" hookless ALUXX wheelsystem, 30mm IW, 40mm OW, 21mm H,72t POE, 28 j-bend spokes, MS driver body
HUBS	Giant TRA 2, F29"-R27.5" hookless ALUXX wheelsystem, 30mm IW, 40mm OW, 21mm H,72t POE, 28 j-bend spokes, MS driver body
SPOKES	Giant TRA 2, F29"-R27.5" hookless ALUXX wheelsystem, 30mm IW, 40mm OW, 21mm H,72t POE, 28 j-bend spokes, MS driver body
TYRES	[F] Maxxis Assegai 29x2.5 WT, 3C MaxxTerra, 60 TPI, EXO+, TR [R] Maxxis Minion DHR II 29 27.5x2,4WT, 3C MaxxTerra, DD 2x60 TPI TR
EXTRAS	MRP AMG CS chain guide for all GSC's, Tubeless Prepared, maximum tyre size 2.5", maximum chainring size 36T
LIMITS	
MAX TYRE CLEARANCE	29x2.5"
MAX CHAINRING SIZE	36T

Price: £2,999.00

GEOMETRY

FRAME	S			M			L			XL		
	LOW HIGH			LOW HIGH			LOW HIGH			LOW HIGH		
Seat Tube Angle	78.3°	78.7°	79.0°	78.3°	78.7°	79.0°	77.3°	77.7°	78.0°	77.3°	77.7°	78.0°
Top Tube Length (mm)	556	555	555	587	586	585	620	620	619	652	652	651
Head Tube Length (mm)	100			105			115			120		
Head Tube Angle	63.5°	63.9°	64.2°	63.5°	63.9°	64.2°	63.5°	63.9°	64.2°	63.5°	63.9°	64.2°
Wheelbase (mm)	1214	1213	1212	1246	1245	1244	1271	1270	1269	1304	1303	1302
Chain Stay Length (mm)	445	443	442	445	443	442	445	443	442	445	443	442
Stack (mm)	627	624	622	632	629	626	641	638	635	645	642	639
Reach (mm)	426	430	434	456	460	464	476	480	484	506	510	514
Stand Over Height (mm)	723	727	732	743	747	752	756	760	765	771	777	782
Crank Length (mm)	165			170			170			170		

Every effort has been made to ensure accuracy throughout this website. However, Giant reserves the right to change bike specifications, features, prices and colours without prior notice.