REIGN SE



SPECS

FRAME	
SIZES	S, M, L, XL
COLOURS	Gilded Terrain
FRAME	ALUXX SL-grade Aluminium front and rear triangles, 165mm Maestro suspension, Flip Chip 2 position, 12x148mm thru-axle, 27.5 rear wheel, integrated downtube storage, 55mm Chainline
FORK	RockShox Zeb Ultimate Charger 3.2, 180mm,15x110mm Maxle Stealth thru-axle
SHOCK	RockShox Vivid Ultimate RCT2, 2 position, custom tuned for Giant
COMPONENTS	
HANDLEBAR	Giant Contact TR35, alloy, 35mm rise
GRIPS	Giant Tactal Pro Single lock-on
STEM	Giant Contact SL 35 S:40mm, M:40mm, L:40mm, XL:40mm
SEATPOST	Giant Contact Switch AT dropper, adjustable travel, remote S: 140-170mm travel / 30.9 x 470mm M: 140-170mm travel / 30.9 x 470mm L: 170-200mm travel / 30.9 x 530mm XL: 170-200mm travel / 30.9 x 530mm
SADDLE	Giant Romero SL
PEDALS	N/A
DRIVETRAIN	
SHIFTERS	SRAM Eagle 90, 1x12
FRONT DERAILLEUR	N/A
REAR DERAILLEUR	SRAM Eagle 90 Transmission
BRAKES	SRAM Maven, hydraulic, SRAM HS2 rotors [F]220mm, [R]200mm
BRAKE LEVERS	SRAM Maven Silver
CASSETTE	SRAM XS-1270 Transmission, 10-52
CHAIN	SRAM 70 Transmission
CRANKSET	SRAM 90 Transmission, 32t, 55mm chainline S:165mm, M:165mm, L:165mm, XL:165mm
BOTTOM BRACKET	SRAM DUB, press fit

WHEELS	
RIMS	Giant TRA Hookless Tubeless ready Alloy Fr: 29", Rr: 27.5" 30mm inner width
HUBS	[F] Giant TRA MTB Alloy Hub, 6 Bolt, 28H [R] Giant TRX MTB Alloy Hub, SRAM XD Drive Body Pawl Driver (Pawl 36x2 T), 28H
SPOKES	Sapim Laser
TYRES	[F] Maxxis Assegai 29x2.5 WT, MaxxTerra, EXO+, TR [R] Maxxis Minion DHR II 27.5x2.4 WT, MaxxTerra, DD, TR tubeless
EXTRAS	Tubeless prepared, MRP AMG chain guide
LIMITS	
MAX TYRE CLEARANCE	2.5"
MAX CHAINRING SIZE	36t

Price: $7,999.00

GEOMETRY

FRAME	S	M	L	XL
	LOW | MID | HIGH	LOW | MID | HIGH	LOW | MID | HIGH	LOW | MID | HIGH
Seat Tube Length (mm)	400	425	450	475
Seat Post Insertion Depth (mm)	257	383	308	333
Seat Tube Angle	78.3° | 78.7° | 79.0°	77.4° | 77.8°	76.4° | 76.8°	76.4° | 76.8°
Top Tube Length (mm)	556 | 555 | 555	589 | 588	623 | 622	655 | 654
Head Tube Length (mm)	100	105	115	120
Head Tube Angle	63.5° | 63.9° | 64.2°	62.6° | 63.0°	62.6° | 63.0°	62.6° | 63.0°
Fork Rake (mm)	44	44	44	44
Trail (mm)	140 | 138 | 135	147 | 145	147 | 145	147 | 144
Wheelbase (mm)	1214 | 1213 | 1212	1251 | 1250	1275 | 1274	1308 | 1307
Chain Stay Length (mm)	445 | 443 | 442	443 | 442	443 | 442	443 | 442
Bottom Bracket Drop (mm)	35 | 30 | 25	20 | 15	20 | 15	21 | 15
Stack (mm)	627 | 624 | 622	639 | 636	648 | 645	653 | 650
Reach (mm)	426 | 430 | 434	446 | 450	466 | 470	497 | 501
Stand Over Height (mm)	723 | 727 | 732	734 | 739	750 | 755	744 | 749
Stem Length (mm)	40	40	40	40
Crank Length (mm)	165	165	165	165
Wheel Size	29" [F], 27.5" [R]	29" [F], 27.5" [R]	29" [F], 27.5" [R]	29" [F], 27.5" [R]

*Please note that our specifications may be impacted by running substitution changes, we highly recommend confirming the specifications of our products with your local retailer at the time of sale if purchasing in-store. *Recommended Retail Prices are subject to change without notice and may vary from store to store depending on freighting and assembly costs.*