



SPECS

FRAME	
SIZES	M, L, XL
COLOURS	Black Lightning/Chrome
FRAME	ALUXX SL-grade aluminum front and rear triangles, 165mm Maestro suspension, flip chip - Maestro, 12x148mm thru-axle, 27.5-inch rear wheel compatible, integrated downtube storage
FORK	RockShox Zeb Ultimate, 180mm, Debonair, Charger 3.1 RC2 damper, 15x110mm, Maxle Stealth
SHOCK	RockShox Vivid Ultimate, RCT2, adjustable hydraulic bottom out, 205/65
COMPONENTS	
HANDLEBAR	Giant Contact TR35, 35mm rise, 35mm
GRIPS	Giant Tactal Pro single lock-on
STEM	Giant Contact SL 35
SEATPOST	Giant Contact Switch AT adjustable dropper, remote M: 140-170mm travel / 30.9 x 470mm L/XL: 170-200mm travel / 30.9 x 530mm
SADDLE	Giant Romero
PEDALS	N/A
DRIVETRAIN	
SHIFTERS	SRAM Eagle 90, mechanical, 1x12
FRONT DERAILLEUR	N/A
REAR DERAILLEUR	SRAM Eagle 90 mechanical transmission
BRAKES	SRAM Maven Silver, 4-piston, hydraulic SRAM HS2 rotors, [F]220mm, [R]200mm
BRAKE LEVERS	SRAM Maven
CASSETTE	SRAM XS-1270 V2 Eagle Transmission, 12-speed, 10x52
CHAIN	SRAM 70 Eagle Transmission
CRANKSET	SRAM 90, 32t, 55mm chainline
BOTTOM BRACKET	SRAM DUB, press fit

WHEELS	
RIMS	Giant TRA 2 6069 alloy, welded, hookless 30mm IW, 40mm OW, 21mm H, Wide Guard technology [F] 29, [R] 27.5
HUBS	[F] Giant MTB alloy, 6-bolt [R] Giant MTB alloy, 72t POE, 6-bolt, 6-pawl, HG-driver
SPOKES	Sapim Laser straight pull, DBL technology
TIRES	[F] Maxxis Assegai 29x2.5" WT, 3C MaxxGrip, DD, TR, 120TPI, folding [R] Maxxis Minion DHR II 27.5x2.4" WT, 3C MaxxGrip, DD, TR, tubeless, 120TPI, folding
EXTRAS	MRP AMG CS chain guide, 3M tailgate protector, integrated down tube storage bag, tubeless prepared, 2.5" max tire size, 36t max chainring size

Suggested Retail Price (CDN): \$6,499.00

FRAME GEOMETRY

FRAME	M	L	XL
	MID HIGH	MID HIGH	MID HIGH
Seat Tube Length (mm)	425	450	475
Seat Post Insertion Depth (mm)	383	308	333
Seat Tube Angle	77.4° 77.8°	76.4° 76.8°	76.4° 76.8°
Top Tube Length (mm)	589 588	623 622	655 654
Head Tube Length (mm)	105	105	120
Head Tube Angle	62.6° 63.0°	62.6° 63.0°	62.6° 63.0°
Fork Rake (mm)	44	44	44
Trail (mm)	147 145	147 145	147 144
Wheelbase (mm)	1251 1250	1275 1274	1308 1307
Chain Stay Length (mm)	443 442	443 442	443 442
Bottom Bracket Drop (mm)	20 15	20 15	21 15
Stack (mm)	639 636	648 645	653 650
Reach (mm)	446 450	466 470	497 501
Stand Over Height (mm)	734 739	750 755	744 749
Handlebar Width (mm)	800	800	800
Stem Length (mm)	40	40	40
Crank Length (mm)	165	165	165
Wheel Size	29" [F] 27.5" [R]	29" [F] 27.5" [R]	29" [F] 27.5" [R]