



SPECS

FRAME	
SIZES	M, L, XL
COLORS	Black Lightning
FRAME	ALUXX SL-Grade Aluminium front and rear triangles, 165mm Maestro suspension, flip chip 2 position, 12x148mm thru-axle, 27.5 rear wheel, integrated downtube storage, 55mm Chainline
FORK	RockShox Zeb Ultimate Charger 3.1, 180mm,15x110 Maxle Stealth, custom tuned for Giant
SHOCK	RockShox Vivid Ultimate, 2 position, custom tuned for Giant
COMPONENTS	
HANDLEBAR	Giant Contact TR35, alloy, 35mm
GRIPS	Giant Tactal Pro Single lock-on
STEM	Giant Contact SL 35 M:40mm, L:40mm, XL:40mm
SEATPOST	Giant Contact Switch AT dropper, adjustable travel, remote M: 140-170mm travel / 30.9 x 470mm L: 170-200mm travel / 30.9 x 530mm XL: 170-200mm travel / 30.9 x 530mm
SADDLE	Giant Romero SL
PEDALS	N/A
DRIVETRAIN	
SHIFTERS	SRAM Eagle 90 1x12sp
FRONT DERAILLEUR	N/A
REAR DERAILLEUR	SRAM Eagle 90 T-Type
BRAKES	SRAM Maven Silver, hydraulic, SRAM HS2 rotors [F]220mm, [R]200mm
BRAKE LEVERS	SRAM Maven Silver
CASSETTE	SRAM XS 1270, 10-52
CHAIN	SRAM 70 T-Type
CRANKSET	SRAM 90 T-Type , 32t, 55mm chainline, M:165mm, L:165mm, XL:165mm
BOTTOM BRACKET	SRAM DUB, press fit

WHEELS	
RIMS	Giant TRA Hookless Tubeless ready Alloy Fr: 29", Rr: 27.5" 30mm inner width
HUBS	Giant TRA MTB Alloy Hub, 6 Bolt, 110x15 [F] / 148x12 SRAM XD Drive Body Pawl Driver (Pawl 36x2 T) Thru-axle [R]
SPOKES	Sapim Laser
TIRES	[F] Maxxis Assegai 29x2.5 WT, 3C MaxxTerra, EXO+, TR [R] Maxxis Minion DHR II 27.5x2.4 WT, 3C MaxxTerra , EXO, TR tubeless
EXTRAS	Tubeless prepared, 2.5" max tyre size, 36t max chainring size, MRP AMG chain guide

Price: \$8,999.00

GEOMETRY

FRAME	M			L			XL		
	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH
Seat Tube Length (mm)	425			450			475		
Seat Post Insertion Depth (mm)	383			308			333		
Seat Tube Angle	77.9° 77.4° 77.8°			77.0° 76.4° 76.8°			77.0° 76.4° 76.8°		
Top Tube Length (mm)	588 589 588			621 623 622			653 655 654		
Head Tube Length (mm)	105			105			120		
Head Tube Angle	63.1° 62.6° 63.5°			63.1° 62.6° 63.5°			63.1° 62.6° 63.5°		
Fork Rake (mm)	44			44			44		
Trail (mm)	147 145			147 145			147 144		
Wheelbase (mm)	1251 1250			1275 1274			1308 1307		
Chain Stay Length (mm)	443 442			443 442			443 442		
Bottom Bracket Drop (mm)	20 15			20 15			21 15		
Stack (mm)	639 636			648 645			653 650		
Reach (mm)	446 450			466 470			497 501		
Stand Over Height (mm)	734 739			750 755			744 749		
Stem Length (mm)	40			40			40		
Crank Length (mm)	165			165			165		
Wheel Size	29" [F] 27.5" [R]			29" [F] 27.5" [R]			29" [F] 27.5" [R]		

Please note that our specifications may be impacted by running substitution changes, we highly recommend confirming the specifications of our products with your local retailer at the time of sale if purchasing in-store. *Recommended Retail Prices are subject to change without notice and may vary from store to store depending on freighting and assembly costs.