

REIGN SE

GIANT



ŠPECIFIKÁCIE

RÁM	
VELKOSTI	S, M, L, XL
FARBY	Gilded Terrain
RÁM	ALUXX SL-grade aluminum front and rear triangles, 165mm Maestro suspension, flip chip, 12x148mm thru-axle, 27.5 or 29-inch rear wheel compatible, flip chip - Maestro 3, integrated down tube storage
VIDLICA	RockShox Zeb Ultimate, Charger 3.2, RC2 damper, 180mm, 15x110, Maxle Stealth, Debonair
TLMIČ	RockShox Vivid Ultimate, RCT2, adjustable hydraulic bottom out, trunnion mount, 205/65
KOMPONENTY	
RIADIDLÁ	Giant Contact TR35, 800x35mm, 35mm rise
GRIPY	Giant Tactal Pro Single
PREDSTAVEC	Giant Contact SL 35 S:40mm, M:40mm, L:40mm, XL:40mm
SEDLOVKA	Contact Switch AT dropper, remote S: 110-140mm travel / 30.9 x 395mm M: 140-170mm travel / 30.9 x 470mm L: 170-200mm travel / 30.9 x 530mm XL: 170-200mm travel / 30.9 x 530mm
SEDADLO	Giant Romero
PEDÁLE	platform [GC,GT]
POHON	
RADENIE	SRAM Eagle 90, 1x12
PREŠMYKAČ	N/A
PREHADZOVAČKA	SRAM Eagle 90 Transmission
BRZDY	SRAM Maven, hydraulic, SRAM HS2 rotors [F]220mm, [R]200mm
BRZDOVÉ PÁKY	SRAM Maven
KAZETA	SRAM XS 1270, 10x52
REŤAZ	SRAM 70
KLUKY	SRAM 90, 32t, 55mm chainline S:165mm, M:165mm, L:165mm, XL:165mm
STREDOVÉ ZLOŽENIE	SRAM DUB, press fit

KOLESÁ	
RÁFIKY	Giant TRA WheelSystem, 6069 alloy, hookless, 30mm inner width, 40mm outer width, 21mm height, Wide Guard Technology
NÁBOJE	[F] Giant MTB alloy, 6-bolt [R] Giant MTB alloy, 72 POE (Points of Engagement), 6-bolt, MicroSpline driver body
ŠPICE	Sapim, 28, straight pull, DBL Technology
PNEUMATIKY	[F] Maxxis Assegai 29x2.5 WT, 3C MaxxGrip, EXO+, TR [R] Maxxis Minion DHR II 27.5x2.4 WT, 3C MaxxGrip, DD, TR tubeless
DOPLNKY	tubeless prepared, 2.5" max tire size, 36t max chainring size, MRP AMG CS chain guide

Cena: 5 299 €

GEOMETRIA

RÁM	S			M			L		
	LOW MID HIGH			LOW MID HIGH			LOW MID HIGH		
Dĺžka sedlovej trubky (mm)	400			425			450		
Hĺbka vloženia sedlovky (mm)	257			383			308		
Uhol sedlovej trubky	78,3° 78,7° 79,0°			78,3° 78,7° 79,0°			77,3° 77,7° 78,0°		
Dĺžka hornej rámovej trubky (mm)	556 555 555			587 586 585			620 620 619		
Dĺžka hlavovej trubky (mm)	100			105			115		
Uhol hlavovej trubky	63,5° 63,9° 64,2°			63,5° 63,9° 64,2°			63,5° 63,9° 64,2°		
Offset vidlice (mm)	44			44			44		
Trail (mm)	140 138 135			140 138 135			140 138 135		
Rázvor (mm)	1214 1213 1212			1246 1245 1244			1271 1270 1269		
Dĺžka zadnej stavby (mm)	445 443 442			445 443 442			445 443 442		
Rozdiel zadnej voči stredovej osi - BB DROP (mm)	35 30 25			35 30 25			35 30 25		
Stack - výška riadenia (mm)	627 624 622			632 629 626			641 638 635		
Reach (mm)	426 430 434			456 460 464			476 480 484		
Výška rámu od zeme (mm)	723 727 732			743 747 752			756 760 765		
Šírka riaditok (mm)	800			800			800		
Dĺžka predstavca (mm)	40			40			40		
Dĺžka klúk (mm)	165			170			170		
Rozmer kolies	29" [F], 27.5" [R]			29" [F], 27.5" [R]			29" [F], 27.5" [R]		

Všetky ceny a špecifikácie sa môžu zmeniť bez predchádzajúceho upozornenia.