



SPECIFIKACIJE

OKVIR	
VELIKOSTI	S, M, L, XL
BARVE	Black Lightning/Chrome
OKVIR	ALUXX SL-grade aluminum front and rear triangles, 165mm Maestro suspension, flip chip, 12x148mm thru-axle, 27.5 or 29-inch rear wheel compatible, flip chip - Maestro 3, integrated down tube storage
VILICE	RockShox Zeb Ultimate, Charger 3.1 RC2 damper, 180mm, 15x110, Maxle Stealth, Debonair
AMORTIZER	RockShox Vivid Ultimate, RCT2, adjustable hydraulic bottom out, trunnion mount, 205/65 S:425#, M:425#, L:450#, XL: 475#
KOMPONENTE	
KRMILO	Giant Contact TR35, 800x35mm, 35mm rise
GRIPS	Giant Tactal Pro Single
OPORA KRMILA	Giant Contact SL 35 S:40mm, M:40mm, L:40mm, XL:40mm
OPORA SEDEŽA	Contact Switch AT dropper, remote S: 110-140mm travel / 30.9 x 395mm
SEDEŽ	Giant Romero
POGON	
PRESTAVNE ROČICE	SRAM Eagle 90, mechanical, 1x12
PREDNJI MENJALNIK	N/A
ZADNJI MENJALNIK	SRAM Eagle 90 mechanical transmission
ZAVORE	SRAM Maven, hydraulic, SRAM HS2 rotors [F]220mm, [R]200mm
ZAVORNE ROČICE	SRAM Maven
VERIŽNIK	SRAM XS 1270, 10x52
VERIGA	SRAM 70
GONILKE Z VERIŽNIKI	SRAM 90, 32t, 55mm chainline S:165mm, M:165mm, L:165mm, XL:165mm
BOTTOM BRACKET	SRAM DUB, press fit

OBROČNIKI	
OBROČI	Giant TRA WheelSystem, 6069 alloy, hookless, 30mm inner width, 40mm outer width, 21mm height, Wide Guard Technology
PESTA	[F] Giant MTB alloy, 6-bolt, [R] Giant MTB alloy, 72 POE (Points of Engagement), 6-bolt, MicroSpline driver body
NAPERE	Sapim, 28, straight pull, DBL Technology
PLAŠČI	[F] Maxxis Assegai 29x2.5 WT, 3C MaxxGrip, EXO+, TR [R] Maxxis Minion DHR II 27.5x2.4 WT, 3C MaxxGrip, DD, TR tubeless
DODATKI	tubeless prepared, 2.5" max tire size, 36t max chainring size, MRP AMG CS chain guide

GEOMETRIJA

OKVIR	M			L			XL		
	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH
Dolžina sedežne cevi (mm)	425			450			475		
Seat Post Insertion Depth (mm)	383			308			333		
Kot sedežne cevi	77,9°	77,4°	77,8°	77,0°	76,4°	76,8°	77,0°	76,4°	76,8°
Top Tube Length (mm)	588 589	588		621 623	622		653 655	654	
Višina glave okvirja (mm)	105			105			120		
Krmilni kot	63,1°	62,6°	63,5°	63,1°	62,6°	63,5°	63,1°	62,6°	63,5°
Zamik vpetja osi (mm)	44			44			44		
Trail (mm)	147 145			147 145			147 144		
Medosna razdalja (mm)	1251 1250			1275 1274			1308 1307		
Dolžina cevi ob verigi (mm)	443 442			443 442			443 442		
Bottom Bracket Drop (mm)	20 15			20 15			21 15		
Oddaljenost zgornje cevi od gonilne osi (mm)	639 636			648 645			653 650		
Doseg (mm)	446 450			466 470			497 501		
Višina zgornje cevi (mm)	734 739			750 755			744 749		
Širina krmila (mm)	800			800			800		
Dolžina opore krmila (mm)	40			40			40		
Dolžina gonilke (mm)	165			165			165		
Velikost obročnikov	29" [F] 27.5" [R]			29" [F] 27.5" [R]			29" [F] 27.5" [R]		

Vse navedene specifikacije se lahko spremenijo brez obvestila.