



ŠPECIFIKÁCIE

RÁM	
RÁM	ALUXX SL-Grade Aluminium front and rear triangles, Maestro Suspension, 160mm travel, 12x148mm thru-axle, integrated storage solution frame size S/XL: 29"F & 29"R commercial spec and 27.5" rear wheel compatible
VIDLICA	NEW RockShox Zeb Delta RC damper 29"Boost 15x110 Maxle Stealth 170mm
TLMIČ	RockShox SuperDeluxe, R, 205x62,5, custom tuned for Giant, recommended sag 30%
KOMPONENTY	
RIADIDLÁ	Giant Contact TR35, 800x35mm, 35mm rise,AL6061
GRIPY	Giant Tactal Pro, single, lock-on
PREDSTAVEC	Giant Contact SL 35, Diameter 35mm, 8 degree
SEDOVKA	Contact Switch AT DSP with remote lever, 30,9mm
SEDADLO	Giant Romero
PEDÁLE	Al body/AL cage Platform (GC,GT)
HLAVOVÉ ZLOŽENIE	NO57
POHON	
RADENIE	NEW Shimano Deore SL M6200, 1x12
PREHADZOVAČKA	NEW Shimano Deore RD M7200, Shadow +
BRZDY	TRP EVO Comp, black HD-M7040 4 piston
BRZDOVÉ PÁKY	TRP EVO Comp
KAZETA	NEW Shimano Deore, CS M6200 10x51
REŤAZ	KMC X12
KLUKY	Praxis Cadet HD M24 Boost, 32T, steel chainring, 55mm chainline with NEW MRP AMG CS Guide, Next generation upper guide
STREDOVÉ ZLOŽENIE	Shimano PressFit Praxis Pressfit

KOLESÁ	
RÁFIKY	Giant TRA 2, F29"-R27.5" hookless ALUXX wheelsystem, 30mm IW, 40mm OW, 21mm H,72t POE, 28 j-bend spokes, MS driver body
NÁBOJE	Giant TRA 2, F29"-R27.5" hookless ALUXX wheelsystem, 30mm IW, 40mm OW, 21mm H,72t POE, 28 j-bend spokes, MS driver body
ŠPICE	Giant TRA 2, F29"-R27.5" hookless ALUXX wheelsystem, 30mm IW, 40mm OW, 21mm H,72t POE, 28 j-bend spokes, MS driver body
PNEUMATIKY	[F] Maxxis Assegai 29x2.5 WT, 3C MaxxTerra, 60 TPI, EXO+, TR [R] Maxxis Minion DHR II 29 27.5x2.4WT, 3C MaxxTerra, DD 2x60 TPI TR
DOPLNKY	MRP AMG CS chain guide for all GSC's, Tubeless Prepared, maximum tire size 2.5", maximum chainring size 36T
LIMITY	
MAXIMÁLNA ŠÍRKA PNEUMATÍK	29x2.5"
MAXIMÁLNA VEĽKOSŤ REŤAZE	36T

Cena: 3 849 €

GEOMETRIA

RÁM	S		M		L		XL	
	LOW HIGH		LOW HIGH		LOW HIGH		LOW HIGH	
Uhol sedlovej trubky	78,3° 78,7°		79,0° 78,3° 78,7°		79,0° 77,3° 77,7°		78,0° 77,3° 77,7°	
Dĺžka hornej rámovej trubky (mm)	556	555 555	587	586 585	620	620 619	652	652 651
Dĺžka hlavovej trubky (mm)	100		105		115		120	
Uhol hlavovej trubky	63,5° 63,9°		64,2° 63,5° 63,9°		64,2° 63,5° 63,9°		64,2° 63,5° 63,9°	
Rázvor (mm)	1214	1213 1212	1246	1245 1244	1271	1270 1269	1304	1303 1302
Dĺžka zadnej stavby (mm)	445	443 442	445	443 442	445	443 442	445	443 442
Stack - výška riadenia (mm)	627	624 622	632	629 626	641	638 635	645	642 640
Reach (mm)	426	430 434	456	460 464	476	480 484	506	510 514
Výška rámu od zeme (mm)	723	727 732	743	747 752	756	760 765	771	777 782
Dĺžka klúk (mm)	165		170		170		170	

Všetky ceny a špecifikácie sa môžu zmeniť bez predchádzajúceho upozornenia.