



SPECIFIKACIJE

OKVIR	
OKVIR	ALUXX SL-Grade Aluminium front and rear triangles, Maestro Suspension, 160mm travel, 12x148mm thru-axle, integrated storage solution frame size S/XL: 29"F & 29"R commercial spec and 27.5" rear wheel compatible
VILICE	NEW RockShox Zeb Delta RC damper 29"Boost 15x110 Maxle Stealth 170mm
AMORTIZER	RockShox SuperDeluxe, R, 205x62,5, custom tuned for Giant, recommended sag 30%
KOMPONENTE	
KRMILO	Giant Contact TR35, 800x35mm, 35mm rise,AL6061
GRIPS	Giant Tactal Pro, single, lock-on
OPORA KRMILA	Giant Contact SL 35, Diameter 35mm, 8 degree
OPORA SEDEŽA	Contact Switch AT DSP with remote lever, 30,9mm
SEDEŽ	Giant Romero
PEDALA	Al body/AL cage Platform (GC,GT)
HEADSET	NO57
POGON	
PRESTAVNE ROČICE	NEW Shimano Deore SL M6200, 1x12
ZADNJI MENJALNIK	NEW Shimano Deore RD M7200, Shadow +
ZAVORE	TRP EVO Comp, black HD-M7040 4 piston
ZAVORNE ROČICE	TRP EVO Comp
VERIŽNIK	NEW Shimano Deore, CS M6200 10x51
VERIGA	KMC X12
GONILKE Z VERIŽNIKI	Praxis Cadet HD M24 Boost, 32T, steel chainring, 55mm chainline with NEW MRP AMG CS Guide, Next generation upper guide
BOTTOM BRACKET	Shimano PressFit Praxis Pressfit

OBROČNIKI	
OBROČI	Giant TRA 2, F29"-R27.5" hookless ALUXX wheelsystem, 30mm IW, 40mm OW, 21mm H,72t POE, 28 j-bend spokes, MS driver body
PESTA	Giant TRA 2, F29"-R27.5" hookless ALUXX wheelsystem, 30mm IW, 40mm OW, 21mm H,72t POE, 28 j-bend spokes, MS driver body
NAPERE	Giant TRA 2, F29"-R27.5" hookless ALUXX wheelsystem, 30mm IW, 40mm OW, 21mm H,72t POE, 28 j-bend spokes, MS driver body
PLAŠČI	[F] Maxxis Assegai 29x2.5 WT, 3C MaxxTerra, 60 TPI, EXO+, TR [R] Maxxis Minion DHR II 29 27.5x2.4WT, 3C MaxxTerra, DD 2x60 TPI TR
DODATKI	MRP AMG CS chain guide for all GSC's, Tubeless Prepared, maximum tire size 2.5", maximum chainring size 36T
LIMITS	
MAX TIRE CLEARANCE	29x2.5"
MAX CHAINRING SIZE	36T

GEOMETRIJA

OKVIR	S			M			L			XL
	LOW HIGH			LOW HIGH			LOW HIGH			LOW HIGH
Kot sedežne cevi	78,3° 78,7° 79,0°			78,3° 78,7° 79,0°			77,3° 77,7° 78,0°			77,3° 77,7° 78,0°
Top Tube Length (mm)	556	555	555	587	586	585	620	620	619	655
Višina glave okvirja (mm)	100			105			115			120
Krmilni kot	63,5°	63,9°	64,2°	63,5°	63,9°	64,2°	63,5°	63,9°	64,2°	63,5°
Medosna razdalja (mm)	1214	1213	1212	1246	1245	1244	1271	1270	1269	1300
Dolžina cevi ob verigi (mm)	445	443	442	445	443	442	445	443	442	445
Oddaljenost zgornje cevi od gonilne osi (mm)	627	624	622	632	629	626	641	638	635	641
Doseg (mm)	426	430	434	456	460	464	476	480	484	500
Višina zgornje cevi (mm)	723	727	732	743	747	752	756	760	765	770
Dolžina gonilke (mm)	165			170			170			175

Vse navedene specifikacije se lahko spremenijo brez obvestila.