



## SPECS

FRAME	
<b>SIZES</b>	S, M, L, XL
<b>COLORS</b>	Concrete/Mulberry Dye
<b>FRAME</b>	ALUXX SL-Grade Aluminum, 146mm Maestro suspension
<b>FORK</b>	Fox 38 Performance Elite, GRIP2, 170mm, 110x15 Kabolt, tapered, 44mm offset, custom tuned for Giant
<b>SHOCK</b>	Fox DHX2 Performance Elite, 205/60, custom tuned for Giant
COMPONENTS	
<b>HANDLEBAR</b>	Giant Contact SL TR35, 800x35mm, 20mm rise
<b>STEM</b>	Giant Contact SL 35
<b>SEATPOST</b>	Giant Contact Switch dropper post with remote, 30.9
<b>SADDLE</b>	Giant Romero
<b>PEDALS</b>	platform
DRIVETRAIN	
<b>SHIFTERS</b>	SRAM NX Eagle
<b>FRONT DERAILLEUR</b>	N/A
<b>REAR DERAILLEUR</b>	SRAM NX Eagle
<b>BRAKES</b>	Shimano SLX
<b>BRAKE LEVERS</b>	Shimano SLX
<b>CASSETTE</b>	SRAM NX Eagle, 11x50
<b>CHAIN</b>	SRAM NX Eagle
<b>CRANKSET</b>	TruVativ Descendent 6k Eagle DUB, 32t with MRP alloy guide
<b>BOTTOM BRACKET</b>	SRAM DUB, press fit

WHEELS	
<b>RIMS</b>	Giant AM 29, tubeless ready sleeve-joint rim, 30mm inner width
<b>HUBS</b>	[F] Giant Tracker Performance Boost 15x110, sealed bearing [R] Giant Tracker Performance Boost 12x148, sealed bearing
<b>SPOKES</b>	Sapim
<b>TIRES</b>	[F] Maxxis Assegai 29x2.5 WT, MaxxTerra, EXO+, TR [R] Maxxis Minion DHR II 29x2.4 WT, MaxxTerra, EXO+, TR tubeless
<b>EXTRAS</b>	tubeless prepared

## GEOMETRY

FRAME	S	M	L	XL
Seat Tube Length (mm)	431	431	464	496
Seat Tube Angle	76,4°	76,4°	76,4°	76,4°
Top Tube Length (mm)	574	601	640	666
Head Tube Length (mm)	100	100	110	120
Head Tube Angle	64,6°	64,6°	64,6°	64,6°
Fork Rake (mm)	44	44	44	44
Trail (mm)	132,7	132,7	132,7	132,7
Wheelbase (mm)	1191	1220	1262	1289
Chain Stay Length (mm)	439	439	439	439
Bottom Bracket Drop (mm)	27	27	27	27
Stack (mm)	622	622	631	640
Reach (mm)	423	451	488	511
Stand Over Height (mm)	757	759	781	804
Handlebar Width (mm)	800	800	800	800
Stem Length (mm)	40	40	40	50
Crank Length (mm)	165	170	170	170
Wheel Size	29"	29"	29"	29"

All specifications listed are subject to change without notice.