



SPECS

FRAME	
SIZES	M, L, XL
COLOURS	Moonstone
FRAME	ALUXX SL-grade aluminum front and rear triangles, 165mm Maestro suspension, flip chip, 12x148mm thru-axle, 27.5-inch rear wheel compatible, flip chip - Maestro 3, integrated down tube storage
FORK	RockShox BoXXer, Charger 3 RC damper, 190mm, 20x110, custom tuned for Giant
SHOCK	RockShox Vivid Base, lockout, 205/65
COMPONENTS	
HANDLEBAR	Giant Contact SL TR35, 800x35mm, 20mm rise
GRIPS	Giant Tactal Pro Single
STEM	TruVativ Descendant Direct Mount 35, 50mm
SEATPOST	Giant Contact, 30.9mm, 400mm
SADDLE	Giant Romero
PEDALS	
DRIVETRAIN	
SHIFTERS	microSHIFT Trail Trigger Pro, 1x10
FRONT DERAILLEUR	N/A
REAR DERAILLEUR	microSHIFT Advent X
BRAKES	TRP EVO DH-R, hydraulic, TRP rotors [F]220mm, [R]200mm
BRAKE LEVERS	TRP EVO DH-R
CASSETTE	microSHIFT Advent X, 11-48
CHAIN	KMC X-10
CRANKSET	Praxis Cadet HD M24, 32t, 165mm, 55mm chainline
BOTTOM BRACKET	Praxis, press fit

WHEELS	
RIMS	Giant TRA 2 wheelset, 6061 alloy, hookless, 30mm inner width, 40mm outer width, 21mm height, Wide Guard Technology
HUBS	[F] Giant MTB alloy, six-bolt, [R] Giant MTB alloy, 72 POE (Points of Engagement), six-bolt, HG driver body
SPOKES	Sapim, 28, J-bend
TYRES	[F] Maxxis Assegai 29x2.5 WT, 3C MaxxTerra, EXO+, TR [R] Maxxis Assegai 27.5x2.5 WT, 3C MaxxGrip, DD, TR tubeless
EXTRAS	tubeless prepared, 2.5" max tire size, 36t max chainring size, MRP AMG CS chain guide

Price: €5,399.00

GEOMETRY

FRAME	M		L		XL	
	MID	HIGH	MID	HIGH	MID	HIGH
Seat Tube Length (mm)	425	450	450	475	475	475
Seat Post Insertion Depth (mm)	383	308	308	333	333	333
Seat Tube Angle	77.9° 78.3°	77.0° 77.3°	77.0° 77.3°	77.0° 77.3°	77.0° 77.3°	77.0° 77.3°
Top Tube Length (mm)	588 587	621 620	621 620	653 652	653 652	653 652
Head Tube Length (mm)	105	115	115	120	120	120
Head Tube Angle	63.1° 63.5°	63.1° 63.5°	63.1° 63.5°	63.1° 63.5°	63.1° 63.5°	63.1° 63.5°
Fork Rake (mm)	56	56	56	56	56	56
Trail (mm)	129.8 127	130 127	130 127	130 127	130 127	130 127
Wheelbase (mm)	1228 1227	1283 1282	1283 1282	1316 1315	1316 1315	1316 1315
Chain Stay Length (mm)	443 442	443 442	443 442	443 442	443 442	443 442
Bottom Bracket Drop (mm)	25 19	25 19	25 19	25 19	25 19	25 19
Stack (mm)	635 632	644 641	644 641	648 645	648 645	648 645
Reach (mm)	452 456	472 476	472 476	503 507	503 507	503 507
Stand Over Height (mm)	737 742	750 755	750 755	766 771	766 771	766 771
Handlebar Width (mm)	800	800	800	800	800	800
Stem Length (mm)	50	50	50	50	50	50
Crank Length (mm)	165	165	165	165	165	165
Wheel Size	F 29 R 27.5	F 29 R 27.5	F 29 R 27.5	F 29 R 27.5	F 29 R 27.5	F 29 R 27.5

All specifications listed are subject to change without notice.