



SPECIFIKACIJE

OKVIR	
VELIKOSTI	M, L, XL
BARVE	Purple/Petra Clay
OKVIR	ALUXX SL-Grade Aluminum front and rear triangles, 165mm Maestro suspension, flip chip, 12x148mm thru-axle, 27.5-inch rear wheel compatible, flip chip - Maestro 3, integrated downtube storage
VILICE	Fox 40 Performance, GRIP damper, 190mm, 20x110, custom tuned for Giant
AMORTIZER	Fox DHX2 Performance Elite, 205/65, custom tuned for Giant S:400#, M:400#, L:450#, XL:500#
KOMPONENTE	
KRMILO	Giant Contact SL TR35, 800x35mm, 20mm rise
GRIPS	Giant Tactal Pro Single S:120mm, M:120mm, L:130mm, XL:130mm
OPORA KRMILA	TruVativ Descendant Direct Mount 35, 50mm
OPORA SEDEŽA	Giant Contact, 30.9mm, 400mm
SEDEŽ	Giant Romero
POGON	
PRESTAVNE ROČICE	Shimano Deore SL-M4100, 1x10
PREDNJI MENJALNIK	N/A
ZADNJI MENJALNIK	Shimano Deore RD-M5120
ZAVORE	SRAM Code R, hydraulic, CenterLine rotors [F]220mm, [R]200mm
ZAVORNE ROČICE	SRAM Code R
VERIŽNIK	Shimano Deore M4100, 11x46
VERIGA	KMC X10
GONILKE Z VERIŽNIKI	Praxis Cadet HD M24, 32t, 165mm, 55mm chainline
BOTTOM BRACKET	Praxis, press fit

OBROČNIKI

OBROČI	Giant AM, alloy
PESTA	Giant Boost, sealed
NAPERE	Sapim
PLAŠČI	[F] Maxxis Assegai 29x2.5 WT, 3C MaxxTerra, EXO+, TR [R] Maxxis Minion DHR II 27.5x2.5 WT, 3C MaxxTerra, DD, TR tubeless
DODATKI	tubeless prepared, 2.5" max tire size, 36t max chainring size, MRP AMG CS chain guide

GEOMETRIJA

OKVIR	M		L		XL	
	MID	HIGH	MID	HIGH	MID	HIGH
Dolžina sedežne cevi (mm)	425	450	475			
Kot sedežne cevi	77,9° 78,3°	77,0° 77,3°	77,0° 77,3°			
Top Tube Length (mm)	588 587	621 620	653 652			
Višina glave okvirja (mm)	105	115	120			
Krmilni kot	63,1° 63,5°	63,1° 63,5°	63,1° 63,5°			
Zamik vpetja osi (mm)	56	56	56			
Trail (mm)	130 127	130 127	130 127			
Medosna razdalja (mm)	1228 1227	1283 1282	1316 1315			
Dolžina cevi ob verigi (mm)	443 442	443 442	443 442			
Bottom Bracket Drop (mm)	25 19	25 19	25 19			
Oddaljenost zgornje cevi od gonilne osi (mm)	635 632	644 641	648 645			
Doseg (mm)	452 456	472 476	503 507			
Višina zgornje cevi (mm)	737 742	750 755	766 771			
Dolžina opore krmila (mm)	50	50	50			
Dolžina gonilke (mm)	165	165	165			
Velikost obročnikov	F29/R27,5	F29/R27,5	F29/R27,5			

Vse navedene specifikacije se lahko spremenijo brez obvestila.