

REVOLT 0



SPECIFIKATIONER

RAMME	
STØRRELSER	S, M, M/L, L, XL
FARVER	Stealth / Chrome
RAMME	ALUXX-grade aluminum, 12x142mm thru-axle, disc, flip chip dropout
FORGAFFEL	Advanced-grade composite, full-composite OverDrive steerer, 12mm thru-axle, disc
KOMPONENTER	
STYR	Giant Contact XR D-Fuse, 31.8mm XS:42cm, S:42cm, M:44cm, M/L:44cm, L:46cm, XL:46cm
GREB / STYRBÅND	cork tape with gel
FREMPIND	Giant Contact, 8-degree XS:50mm, S:60mm, M:70mm, M/L:80mm, L:80mm, XL:90mm
SADELPIND	Giant D-Fuse, alloy, 14mm offset
SADEL	Giant Grit
GEARGRUPPE	
SKIFTEGREB	Shimano GRX RX-610, 2x12
FORSKIFTER	Shimano GRX RX-820
BAGSKIFTER	Shimano GRX RX-820
BREMSE	Shimano GRX RX-410 hydraulic, Giant MPH rotors [F]160mm, [R]160mm
BREMSEGREB	Shimano GRX RX-610 hydraulic
KASSETTE	Shimano 105, 11x34
KÆDE	KMC X12L-1
KRANKSÆT	Shimano FC-RX610-2, 30/46 XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175mm
KRANKBOKS	Shimano, threaded

HJUL	
FÆLGE	Giant S-X2 , alloy
NAV	Giant alloy, 12mm thru-axle
EGER	stainless
DÆK	CrossCut GRIP 1; 700x40c
EKSTRA	tubeless prepared, 53mm max tire size in "long" flip chip position, 45mm max tire size in "short" flip chip position
GRÆNSER	
MAX DÆKSTØRRELSE	53mm

Pris: 15.899,00 kr.

GEOMETRI

RAMME	S		M		ML		L		XL	
	LOW HIGH		LOW HIGH		LOW HIGH		LOW HIGH		LOW HIGH	
Sadelrørslængde (mm)	450		470		490		510		530	
Sadelrørsvinkel	73,5°		73,5°		73,0°		73,0°		73,0°	
Overrørslængde (mm)	550		560		575		585		600	
Kronrørslængde (mm)	135		150		165		180		195	
Kronrørsvinkel	71,0°		71,5°		72,0°		72,0°		72,0°	
Forgaffel fremspring (rake) (mm)	50		50		50		50		50	
Sti (mm)	72 75		68 72		65 68		65 68		65 68	
Akselafstand (mm)	1025 1035		1030 1040		1035 1045		1045 1055		1061 1071	
Kædestagslængde (mm)	430 440		430 440		430 440		430 440		430 440	
Krankboks drop (mm)	80 81		80 81		80 81		80 81		80 81	
Stack (mm)	570		586		602		616		630	
Reach (mm)	381		387		391		397		407	
Skridthøjde (mm)	734 741		752 759		769 776		786 793		801 810	
Styrbredde (mm)	420		440		440		460		460	
Frempindslængde (mm)	60		70		80		80		90	
Pedalarmslængde (mm)	170		172,5		172,5		175		175	
Hjulstørrelse	700x 42C		700x 42C		700x 42C		700x 42C		700x 42C	

Alle de anførte specifikationer kan ændres uden varsel.