



SPEZIFIKATIONEN

RAHMEN	
GRÖSSEN	XS, S, M, M/L, L, XL
FARBE	Stealth / Chrome, Ocean Wave
RAHMEN	ALUXX-grade aluminum, 12x142mm thru-axle, disc, flip chip dropout
GABEL	Advanced-grade composite, full-composite OverDrive steerer, 12mm thru-axle, disc
KOMPONENTEN	
LENKER	Giant Contact XR D-Fuse, 31.8mm XS:42cm, S:42cm, M:44cm, M/L:44cm, L:46cm, XL:46cm
GRIFFE	cork tape with gel
VORBAU	Giant Contact, 8-degree XS:50mm, S:60mm, M:70mm, M/L:80mm, L:80mm, XL:90mm
SATTELSTÜTZE	Giant D-Fuse, alloy, 14mm offset
SATTEL	Giant Grit
ANTRIEB	
SCHALTHEBEL	Shimano GRX RX-610, 2x12
UMWERFER	Shimano GRX RX-820
SCHALTWERK	Shimano GRX RX-820
BREMSEN	Shimano GRX RX-410 hydraulic, Giant MPH rotors [F]160mm, [R]160mm
BREMSHEBEL	Shimano GRX RX-610 hydraulic
KASSETTE	Shimano 105, 11x34
KETTE	KMC X12L-1
KURBEL	Shimano FC-RX610-2, 30/46 XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175mm
TRETLAGER	Shimano, threaded

LAUFRÄDER	
FELGEN	Giant S-X2 , alloy
NABE	Giant alloy, 12mm thru-axle
SPEICHEN	stainless
REIFEN	CrossCut GRIP 1; 700x45c
EXTRAS	tubeless prepared, 53mm max tire size in "long" flip chip position, 45mm max tire size in "short" flip chip position
LIMITS	
MAX TIRE CLEARANCE	53mm

GEOMETRIEDATEN

RAHMEN	XS		S		M		ML		L		XL	
	LOW	HIGH	LOW	HIGH	LOW	HIGH	LOW	HIGH	LOW	HIGH	LOW	HIGH
Sitzrohrlänge (mm)	430	450	430	450	470	490	490	510	510	530	530	550
Sitzrohrwinkel	74.0°	73.5°	73.5°	73.0°	73.0°	73.0°	73.0°	73.0°	73.0°	73.0°	73.0°	73.0°
Oberrohrlänge (mm)	540	550	560	575	585	600	600	615	625	640	640	655
Steuerrohr-Länge (mm)	125	135	150	165	180	195	195	210	220	235	235	250
Steuerrohr-Winkel	70.0°	71.0°	71.5°	72.0°	72.0°	72.0°	72.0°	72.0°	72.0°	72.0°	72.0°	72.0°
Gabelneigung (mm)	50	50	50	50	50	50	50	50	50	50	50	50
Trail (mm)	78 82	72 75	68 72	65 68	65 68	65 68	65 68	65 68	65 68	65 68	65 68	65 68
Radstand (mm)	1029 1039	1025 1035	1030 1040	1035 1045	1045 1055	1061 1071	1061 1071	1071 1081	1081 1091	1091 1101	1101 1111	1111 1121
Kettenstreben-Länge (mm)	430 440	430 440	430 440	430 440	430 440	430 440	430 440	430 440	430 440	430 440	430 440	430 440
Tretlager-Höhe (mm)	80 81	80 81	80 81	80 81	80 81	80 81	80 81	80 81	80 81	80 81	80 81	80 81
Stack (mm)	556	570	586	602	616	630	630	644	658	672	672	686
Reach (mm)	381	381	387	391	397	407	407	413	423	433	433	443
Überstandshöhe (mm)	717 724	734 741	752 759	769 776	786 793	801 810	801 810	817 824	834 841	851 858	851 858	867 874
Lenkerbreite (mm)	420	420	440	440	460	460	460	460	460	460	460	460
Vorbaulänge (mm)	50	60	70	80	80	90	90	90	90	90	90	90
Kurbellänge (mm)	170	170	172.5	172.5	175	175	175	175	175	175	175	175
Radgrösse	700x 42C	700x 42C	700x 42C	700x 42C	700x 42C	700x 42C	700x 42C	700x 42C	700x 42C	700x 42C	700x 42C	700x 42C

Spezifikations-, Preis- und Farbänderungen vorbehalten.