

# REVOLT 0



## SPECS

FRAME	
<b>SIZES</b>	XS, S, M, M/L, L, XL
<b>COLOURS</b>	Stealth / Chrome, Ocean Wave
<b>FRAME</b>	ALUXX-grade aluminum, 12x142mm thru-axle, disc, flip chip dropout
<b>FORK</b>	Advanced-grade composite, full-composite OverDrive steerer, 12mm thru-axle, disc
COMPONENTS	
<b>HANDLEBAR</b>	Giant Contact XR D-Fuse, 31.8mm XS:42cm, S:42cm, M:44cm, M/L:44cm, L:46cm, XL:46cm
<b>GRIPS</b>	cork tape with gel
<b>STEM</b>	Giant Contact, 8-degree XS:50mm, S:60mm, M:70mm, M/L:80mm, L:80mm, XL:90mm
<b>SEATPOST</b>	Giant D-Fuse, alloy, 14mm offset
<b>SADDLE</b>	Giant Grit
DRIVETRAIN	
<b>SHIFTERS</b>	Shimano GRX RX-610, 2x12
<b>FRONT DERAILLEUR</b>	Shimano GRX RX-820
<b>REAR DERAILLEUR</b>	Shimano GRX RX-820
<b>BRAKES</b>	Shimano GRX RX-410 hydraulic, Giant MPH rotors [F]160mm, [R]160mm
<b>BRAKE LEVERS</b>	Shimano GRX RX-610 hydraulic
<b>CASSETTE</b>	Shimano 105, 11x34
<b>CHAIN</b>	KMC X12L-1
<b>CRANKSET</b>	Shimano FC-RX610-2, 30/46 XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175mm
<b>BOTTOM BRACKET</b>	Shimano, threaded

WHEELS	
<b>RIMS</b>	Giant S-X2, alloy
<b>HUBS</b>	Giant alloy, 12mm thru-axle
<b>SPOKES</b>	stainless
<b>TIRES</b>	Giant Crosscut Grip 1, tubeless, 700x40c, 60TPI, folding
<b>EXTRAS</b>	tubeless prepared, 53mm max tire size in "long" flip chip position, 45mm max tire size in "short" flip chip position
LIMITS	
<b>MAX TIRE CLEARANCE</b>	53mm

**Suggested Retail Price (CDN): \$2,699.00**

## FRAME GEOMETRY

FRAME	XS	S	M	ML	L	XL
	SHORT	LONG SHORT	LONG SHORT	LONG SHORT	LONG SHORT	LONG SH
Seat Tube Length (mm)	430	450	470	490	510	530
Seat Tube Angle	74.0°	73.5°	73.5°	73.0°	73.0°	73.0°
Top Tube Length (mm)	540	550	560	575	585	600
Head Tube Length (mm)	125	135	150	165	180	190
Head Tube Angle	70.0°	71.0°	71.5°	72.0°	72.0°	72.0°
Fork Rake (mm)	50	50	50	50	50	50
Trail (mm)	78   82	72   75	68   72	65   68	65   68	65
Wheelbase (mm)	1029   1039	1025   1035	1030   1040	1035   1045	1045   1055	1060
Chain Stay Length (mm)	430   440	430   440	430   440	430   440	430   440	430
Bottom Bracket Drop (mm)	80   81	80   81	80   81	80   81	80   81	80
Stack (mm)	556	570	586	602	616	630
Reach (mm)	381	381	387	391	397	400
Stand Over Height (mm)	717   724	734   741	752   759	769   776	786   793	800
Handlebar Width (mm)	420	420	440	440	460	460
Stem Length (mm)	50	60	70	80	80	90
Crank Length (mm)	170	170	172.5	172.5	175	175
Wheel Size	700x 42C	700x 42C	700x 42C	700x 42C	700x 42C	700x 42C

*All prices and specifications are subject to change without notice.*