

REVOLT 0



SPECS

RAMME	
STØRRELSE	XS, S, M, M/L, L, XL
FARGE	Stealth / Chrome, Ocean Wave
RAMME	ALUXX-grade aluminum, 12x142mm thru-axle, disc, flip chip dropout
GAFFEL	Advanced-grade composite, full-composite OverDrive steerer, 12mm thru-axle, disc
KOMPONENTER	
STYRE	Giant Contact XR D-Fuse, 31.8mm XS:42cm, S:42cm, M:44cm, M/L:44cm, L:46cm, XL:46cm
GRIPS	cork tape with gel
STYRSTEM	Giant Contact, 8-degree XS:50mm, S:60mm, M:70mm, M/L:80mm, L:80mm, XL:90mm
SETEPINNE	Giant D-Fuse, alloy, 14mm offset
SADEL	Giant Grit
DRIVVERK	
GIRHENDLER	Shimano GRX RX-610, 2x12
FRONTGIR	Shimano GRX RX-820
BAKGIR	Shimano GRX RX-820
BREMSE	Shimano GRX RX-410 hydraulic, Giant MPH rotors [F]160mm, [R]160mm
BREMSEHENDLER	Shimano GRX RX-610 hydraulic
KASSETT	Shimano 105, 11x34
KJEDE	KMC X12L-1
KRANK	Shimano FC-RX610-2, 30/46 XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175mm
BOTTOM BRACKET	Shimano, threaded

HJUL	
FELG	Giant S-X2, alloy
NAV	Giant alloy, 12mm thru-axle
EIKE	stainless
DEKK	CrossCut GRIP 1; 700x45c
EXTRAS	tubeless prepared, 53mm max tire size in "long" flip chip position, 45mm max tire size in "short" flip chip position
LIMITS	
MAX TIRE CLEARANCE	53mm

GEOMETRI

RAMME	XS		S		M		ML		L		XL	
	LOW	HIGH	LOW	HIGH	LOW	HIGH	LOW	HIGH	LOW	HIGH	LOW	HIGH
Seat Tube Length (mm)	430	450	430	450	470	490	490	510	510	530	530	550
Seat Tube Angle	74,0°	73,5°	73,5°	73,5°	73,0°	73,0°	73,0°	73,0°	73,0°	73,0°	73,0°	73,0°
Top Tube Length (mm)	540	550	560	575	585	600	600	615	625	640	640	655
Head Tube Length (mm)	125	135	150	165	180	195	195	210	210	225	225	240
Head Tube Angle	70,0°	71,0°	71,5°	72,0°	72,0°	72,0°	72,0°	72,0°	72,0°	72,0°	72,0°	72,0°
Fork Rake (mm)	50	50	50	50	50	50	50	50	50	50	50	50
Trail (mm)	78 82	72 75	68 72	65 68	65 68	65 68	65 68	65 68	65 68	65 68	65 68	65 68
Wheelbase (mm)	1029 1039	1025 1035	1030 1040	1035 1045	1045 1055	1061 1071	1061 1071	1071 1081	1071 1081	1081 1091	1081 1091	1091 1101
Chain Stay Length (mm)	430 440	430 440	430 440	430 440	430 440	430 440	430 440	430 440	430 440	430 440	430 440	430 440
Bottom Bracket Drop (mm)	80 81	80 81	80 81	80 81	80 81	80 81	80 81	80 81	80 81	80 81	80 81	80 81
Stack (mm)	556	570	586	602	616	630	630	646	646	662	662	678
Reach (mm)	381	381	387	391	397	407	407	413	413	419	419	425
Stand Over Height (mm)	717 724	734 741	752 759	769 776	786 793	801 810	801 810	817 824	817 824	833 840	833 840	849 856
Handlebar Width (mm)	420	420	440	440	460	460	460	460	460	460	460	460
Stem Length (mm)	50	60	70	80	80	90	90	90	90	90	90	90
Crank Length (mm)	170	170	172,5	172,5	175	175	175	175	175	175	175	175
Wheel Size	700x 42C	700x 42C	700x 42C	700x 42C	700x 42C	700x 42C	700x 42C	700x 42C	700x 42C	700x 42C	700x 42C	700x 42C

Alle spesifikasjonene kan endres uten varsel.