

REVOLT 0



SPECIFIKACIJE

OKVIR	
VELIKOSTI	XS, S, M, M/L, L, XL
BARVE	Stealth / Chrome, Ocean Wave
OKVIR	ALUXX-grade aluminum, 12x142mm thru-axle, disc, flip chip dropout
VILICE	Advanced-grade composite, full-composite OverDrive steerer, 12mm thru-axle, disc
KOMPONENTE	
KRMILO	Giant Contact XR D-Fuse, 31.8mm XS:42cm, S:42cm, M:44cm, M/L:44cm, L:46cm, XL:46cm
GRIPS	cork tape with gel
OPORA KRMILA	Giant Contact, 8-degree XS:50mm, S:60mm, M:70mm, M/L:80mm, L:80mm, XL:90mm
OPORA SEDEŽA	Giant D-Fuse, alloy, 14mm offset
SEDEŽ	Giant Grit
POGON	
PRESTAVNE ROČICE	Shimano GRX RX-610, 2x12
PREDNJI MENJALNIK	Shimano GRX RX-820
ZADNJI MENJALNIK	Shimano GRX RX-820
ZAVORE	Shimano GRX RX-410 hydraulic, Giant MPH rotors [F]160mm, [R]160mm
ZAVORNE ROČICE	Shimano GRX RX-610 hydraulic
VERIŽNIK	Shimano 105, 11x34
VERIGA	KMC X12L-1
GONILKE Z VERIŽNIKI	Shimano FC-RX610-2, 30/46 XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175mm
BOTTOM BRACKET	Shimano, threaded

OBROČNIKI	
OBROČI	Giant S-X2, alloy
PESTA	Giant alloy, 12mm thru-axle
NAPERE	stainless
PLAŠČI	CrossCut GRIP 1; 700x45c
DODATKI	tubeless prepared, 53mm max tire size in "long" flip chip position, 45mm max tire size in "short" flip chip position
LIMITS	
MAX TIRE CLEARANCE	53mm

GEOMETRIJA

OKVIR	XS		S		M		ML		L	
	LOW	HIGH	LOW	HIGH	LOW	HIGH	LOW	HIGH	LOW	HIGH
Dolžina sedežne cevi (mm)	430	450	470	490	510					
Kot sedežne cevi	74,0°	73,5°	73,5°	73,0°	73,0°					
Top Tube Length (mm)	540	550	560	575	585					
Višina glave okvirja (mm)	125	135	150	165	180					
Krmilni kot	70,0°	71,0°	71,5°	72,0°	72,0°					
Zamik vpetja osi (mm)	50	50	50	50	50					
Trail (mm)	78 82	72 75	68 72	65 68	65 68					
Medosna razdalja (mm)	1029 1039	1025 1035	1030 1040	1035 1045	1045 1055					
Dolžina cevi ob verigi (mm)	430 440	430 440	430 440	430 440	430 440					
Bottom Bracket Drop (mm)	80 81	80 81	80 81	80 81	80 81					
Oddaljenost zgornje cevi od gonilne osi (mm)	556	570	586	602	616					
Doseg (mm)	381	381	387	391	397					
Višina zgornje cevi (mm)	717 724	734 741	752 759	769 776	786 793					
Širina krmila (mm)	420	420	440	440	460					
Dolžina opore krmila (mm)	50	60	70	80	80					
Dolžina gonilke (mm)	170	170	172,5	172,5	175					
Velikost obročnikov	700x 42C	700x 42C	700x 42C	700x 42C	700x 42C					

Vse navedene specifikacije se lahko spremenijo brez obvestila.