

REVOLT 1



SPEZIFIKATIONEN

RAHMEN	
GRÖSSEN	XS, S, M, M/L, L, XL
FARBE	Alpine Green, Bali Bricks
RAHMEN	ALUXX-grade aluminum, 12x142mm thru-axle, disc, flip chip dropout
GABEL	Advanced-grade composite, full-composite OverDrive steerer, 12mm thru-axle, disc
KOMPONENTEN	
LENKER	Giant Contact XR D-Fuse, 31.8mm XS:42cm, S:42cm, M:44cm, M/L:44cm, L:46cm, XL:46cm
GRIFFE	cork tape with gel
VORBAU	Giant Contact, 8-degree XS:50mm, S:60mm, M:70mm, M/L:80mm, L:80mm, XL:90mm
SATTELSTÜTZE	Giant D-Fuse, alloy, 14mm offset
SATTEL	Giant Grit
ANTRIEB	
SCHALTHEBEL	Shimano CUES U6030, 2x10
UMWERFER	Shimano CUES U6030
SCHALTWERK	Shimano CUES U6020
BREMSEN	Shimano CUES U6030 hydraulic, Giant MPH rotors [F]160mm, [R]160mm
BREMSHEBEL	Shimano CUES U6030 hydraulic
KASSETTE	Shimano CS-LG300, 11x39
KETTE	KMC X11
KURBEL	Shimano FC-U6030-2, 32/46 XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175mm
TRETLAGER	Shimano, threaded

LAUFRÄDER	
FELGEN	Giant S-X2, alloy
NABE	Giant alloy, 12mm thru-axle
SPEICHEN	stainless
REIFEN	CrossCut GRIP 1; 700x45c
EXTRAS	tubeless prepared, 53mm max tire size in "long" flip chip position, 45mm max tire size in "short" flip chip position
LIMITS	
MAX TIRE CLEARANCE	53mm

GEOMETRIEDATEN

RAHMEN	XS		S		M		ML		L		XL	
	LOW	HIGH	LOW	HIGH	LOW	HIGH	LOW	HIGH	LOW	HIGH	LOW	HIGH
Sitzrohrlänge (mm)	430	450	470	490	510	530						
Sitzrohrwinkel	74.0°	73.5°	73.5°	73.0°	73.0°	73.0°						
Oberrohrlänge (mm)	540	550	560	575	585	600						
Steuerrohr-Länge (mm)	125	135	150	165	180	195						
Steuerrohr-Winkel	70.0°	71.0°	71.5°	72.0°	72.0°	72.0°						
Gabelneigung (mm)	50	50	50	50	50	50						
Trail (mm)	78 82	72 75	68 72	65 68	65 68	65 68						
Radstand (mm)	1029 1039	1025 1035	1030 1040	1035 1045	1045 1055	1061 1071						
Kettenstreben-Länge (mm)	430 440	430 440	430 440	430 440	430 440	430 440						
Tretlager-Höhe (mm)	80 81	80 81	80 81	80 81	80 81	80 81						
Stack (mm)	556	570	586	602	616	630						
Reach (mm)	381	381	387	391	397	407						
Überstandshöhe (mm)	717 724	734 741	752 759	769 776	786 793	801 810						
Lenkerbreite (mm)	420	420	440	440	460	460						
Vorbaulänge (mm)	50	60	70	80	80	90						
Kurbellänge (mm)	170	170	172.5	172.5	175	175						
Radgrösse	700x 42C	700x 42C	700x 42C	700x 42C	700x 42C	700x 42C						

Spezifikations-, Preis- und Farbänderungen vorbehalten.