

REVOLT 1

GIANT



ESPECIFICACIONES

| CUADRO               |                                                                                        |
|----------------------|----------------------------------------------------------------------------------------|
| TALLAS               | XS, S, M, M/L, L, XL                                                                   |
| COLORES              | Alpine Green                                                                           |
| CUADRO               | ALUXX-grade aluminum, 12x142mm thru-axle, disc, flip chip dropout                      |
| HORQUILLA            | Advanced-grade composite, full-composite OverDrive steerer, 12mm thru-axle, disc       |
| COMPONENTES          |                                                                                        |
| MANILLAR             | Giant Contact XR D-Fuse, 31.8mm XS:42cm, S:42cm, M:44cm, M/L:44cm, L:46cm, XL:46cm     |
| PUÑOS                | cork tape with gel                                                                     |
| POTENCIA             | Giant Contact, 8-degree XS:50mm, S:60mm, M:70mm, M/L:80mm, L:80mm, XL:90mm             |
| TIJA DE SILLÍN       | Giant D-Fuse, alloy, 14mm offset                                                       |
| SILLÍN               | Giant Grit                                                                             |
| TRANSMISIÓN          |                                                                                        |
| MANETAS DE CAMBIO    | Shimano CUES U6030, 2x10                                                               |
| DESVIADOR            | Shimano CUES U6030                                                                     |
| CAMBIO TRASERO       | Shimano CUES U6020                                                                     |
| FRENOS               | Shimano CUES U6030 hydraulic, Giant MPH rotors [F]160mm, [R]160mm                      |
| PALANCAS DE FRENOS   | Shimano CUES U6030 hydraulic                                                           |
| CASETTE              | Shimano CS-LG300, 11x39                                                                |
| CADENA               | KMC X11                                                                                |
| JGO. PLATOS Y BIELAS | Shimano FC-U6030-2, 32/46 XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175mm |
| CAJA DE PEDALIER     | Shimano, threaded                                                                      |

| RUEDAS                      |                                                                                                                      |
|-----------------------------|----------------------------------------------------------------------------------------------------------------------|
| LLANTAS                     | Giant S-X2, alloy                                                                                                    |
| BUJES                       | Giant alloy, 12mm thru-axle                                                                                          |
| RADIOS                      | stainless                                                                                                            |
| CUBIERTAS                   | CrossCut GRIP 1; 700x45c                                                                                             |
| EXTRAS                      | tubeless prepared, 53mm max tire size in "long" flip chip position, 45mm max tire size in "short" flip chip position |
| LÍMITES                     |                                                                                                                      |
| MÁXIMA ANCHURA DE NEUMÁTICO | 53mm                                                                                                                 |

Precio: 1.699,00 €

GEOMETRÍA

| CUADRO                                   | XS                  | S                   | M                   | ML                  | L                   | XL                  |
|------------------------------------------|---------------------|---------------------|---------------------|---------------------|---------------------|---------------------|
|                                          | LOW   HIGH          | LOW   HIGH          | LOW   HIGH          | LOW   HIGH          | LOW   HIGH          | LOW   HIGH          |
| Longitud del tubo del sillín (mm)        | 430                 | 450                 | 470                 | 490                 | 510                 | 530                 |
| Ángulo del tubo del sillín               | 74,0°               | 73,5°               | 73,5°               | 73,0°               | 73,0°               | 73,0°               |
| Longitud del tubo superior (mm) (mm)     | 540                 | 550                 | 560                 | 575                 | 585                 | 600                 |
| Longitud del tubo de dirección (mm) (mm) | 125                 | 135                 | 150                 | 165                 | 180                 | 190                 |
| Ángulo del tubo de dirección             | 70,0°               | 71,0°               | 71,5°               | 72,0°               | 72,0°               | 72,0°               |
| Inclinación de la horquilla (mm)         | 50                  | 50                  | 50                  | 50                  | 50                  | 50                  |
| Trail (mm) (mm)                          | 78   82             | 72   75             | 68   72             | 65   68             | 65   68             | 65   68             |
| Distancia entre ejes (mm) (mm)           | 1029   1039         | 1025   1035         | 1030   1040         | 1035   1045         | 1045   1055         | 1055   1065         |
| Longitud de la vaina (mm) (mm)           | 430   440           | 430   440           | 430   440           | 430   440           | 430   440           | 430   440           |
| Caída del eje de pedalier (mm) (mm)      | 80   81             | 80   81             | 80   81             | 80   81             | 80   81             | 80   81             |
| Stack (mm) (mm)                          | 556                 | 570                 | 586                 | 602                 | 616                 | 630                 |
| Reach (mm) (mm)                          | 381                 | 381                 | 387                 | 391                 | 397                 | 400                 |
| Altura del suelo al tubo (mm) (mm)       | 717   724           | 734   741           | 752   759           | 769   776           | 786   793           | 800   807           |
| Ancho del manillar (mm) (mm)             | 420                 | 420                 | 440                 | 440                 | 460                 | 460                 |
| Longitud de la potencia (mm) (mm)        | 50                  | 60                  | 70                  | 80                  | 80                  | 90                  |
| Longitud de las bielas (mm) (mm)         | 170                 | 170                 | 172,5               | 172,5               | 175                 | 175                 |
| Tamaño de ruedas                         | 700x 42C   700x 42C | 700x 42C   700x 42C | 700x 42C   700x 42C | 700x 42C   700x 42C | 700x 42C   700x 42C | 700x 42C   700x 42C |

Giant se reserva el derecho a modificar especificaciones, precios o colores sin previo aviso.