

REVOLT 1

GIANT



SPECS

FRAME	
SIZES	XS, S, M, M/L, L, XL
COLORS	Alpine Green, Bali Bricks
FRAME	ALUXX-grade aluminum, 12x142mm thru-axle, disc, flip chip dropout
FORK	Advanced-grade composite, full-composite OverDrive steerer, 12mm thru-axle, disc
COMPONENTS	
HANDLEBAR	Giant Contact XR D-Fuse, 31.8mm XS:42cm, S:42cm, M:44cm, M/L:44cm, L:46cm, XL:46cm
GRIPS	cork tape with gel
STEM	Giant Contact, 8-degree XS:50mm, S:60mm, M:70mm, M/L:80mm, L:80mm, XL:90mm
SEATPOST	Giant D-Fuse, alloy, 14mm offset
SADDLE	Giant Grit
DRIVETRAIN	
SHIFTERS	Shimano CUES U6030, 2x10
FRONT DERAILLEUR	Shimano CUES U6030
REAR DERAILLEUR	Shimano CUES U6020
BRAKES	Shimano CUES U6030 hydraulic, Giant MPH rotors [F]160mm, [R]160mm
BRAKE LEVERS	Shimano CUES U6030 hydraulic
CASSETTE	Shimano CS-LG300, 11x39
CHAIN	KMC X11
CRANKSET	Shimano FC-U6030-2, 32/46 XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175mm
BOTTOM BRACKET	Shimano, threaded

WHEELS	
RIMS	Giant S-X2, alloy
HUBS	Giant alloy, 12mm thru-axle
SPOKES	stainless
TIRES	CrossCut GRIP 1; 700x45c
EXTRAS	tubeless prepared, 53mm max tire size in "long" flip chip position, 45mm max tire size in "short" flip chip position
LIMITS	
MAX TIRE CLEARANCE	53mm

GEOMETRY

FRAME	XS		S		M		ML		L		XL	
	LOW	HIGH	LOW	HIGH	LOW	HIGH	LOW	HIGH	LOW	HIGH	LOW	HIGH
Seat Tube Length (mm)	430	450	430	450	470	490	490	510	510	530	530	550
Seat Tube Angle	74,0°	73,5°	73,5°	73,0°	73,0°	73,0°	73,0°	73,0°	73,0°	73,0°	73,0°	73,0°
Top Tube Length (mm)	540	550	560	575	585	600	600	610	610	620	620	630
Head Tube Length (mm)	125	135	150	165	180	195	195	205	205	215	215	225
Head Tube Angle	70,0°	71,0°	71,5°	72,0°	72,0°	72,0°	72,0°	72,0°	72,0°	72,0°	72,0°	72,0°
Fork Rake (mm)	50	50	50	50	50	50	50	50	50	50	50	50
Trail (mm)	78 82	72 75	68 72	65 68	65 68	65 68	65 68	65 68	65 68	65 68	65 68	65 68
Wheelbase (mm)	1029 1039	1025 1035	1030 1040	1035 1045	1045 1055	1061 1071	1061 1071	1061 1071	1061 1071	1061 1071	1061 1071	1061 1071
Chain Stay Length (mm)	430 440	430 440	430 440	430 440	430 440	430 440	430 440	430 440	430 440	430 440	430 440	430 440
Bottom Bracket Drop (mm)	80 81	80 81	80 81	80 81	80 81	80 81	80 81	80 81	80 81	80 81	80 81	80 81
Stack (mm)	556	570	586	602	616	630	630	640	640	650	650	660
Reach (mm)	381	381	387	391	397	407	407	417	417	427	427	437
Stand Over Height (mm)	717 724	734 741	752 759	769 776	786 793	801 810	801 810	811 818	811 818	821 828	821 828	831 838
Handlebar Width (mm)	420	420	440	440	460	460	460	460	460	460	460	460
Stem Length (mm)	50	60	70	80	80	90	90	90	90	90	90	90
Crank Length (mm)	170	170	172,5	172,5	175	175	175	175	175	175	175	175
Wheel Size	700x 42C	700x 42C	700x 42C	700x 42C	700x 42C	700x 42C	700x 42C	700x 42C	700x 42C	700x 42C	700x 42C	700x 42C

All specifications listed are subject to change without notice.