

REVOLT 1

GIANT



TEKNISET TIEDOT

| RUNKO | |
|----------------|---|
| KOOT | XS, S, M, M/L, L, XL |
| VÄRIT | Metal/Shoreline, Pale Olive |
| RUNKO | ALUXX-grade aluminum, 12x142mm thru-axle, disc, flip chip dropout |
| HAARUKKA | Advanced-grade composite, full-composite OverDrive steerer, 12mm thru-axle, disc |
| KOMONENTIT | |
| OHJAUSTANKO | Giant Contact XR D-Fuse, 31.8mm XS:42cm, S:42cm, M:44cm, M/L:44cm, L:46cm, XL:46cm |
| GRIPIT | cork tape with gel |
| OHJAINKANNATIN | Giant Contact, 8-degree XS:50mm, S:60mm, M:70mm, M/L:80mm, L:80mm, XL:90mm |
| SATULATOLPPA | Giant D-Fuse, alloy, 14mm offset |
| SATULA | Giant Approach |
| VOIMANSIIRTO | |
| VAIHDEVIPU | Shimano GRX RX-400, 2x10 |
| ETUVAIHTAJA | Shimano Tiagra |
| TAKAVAIHTAJA | Shimano GRX RX-400 |
| JARRUT | Shimano GRX RX-400 hydraulic, Giant MPH rotors [F]160mm, [R]160mm |
| JARRUKAHVAT | Shimano GRX RX-400 hydraulic |
| RATASPAKKA | Shimano HG500, 11x34 |
| KETJUT | KMC X10 with Missing Link |
| KAMPISARJA | FSA Omega Adventure, 32/48 XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175mm |
| KESKIÖ | FSA Mega EXO |

| RENKAAT | |
|----------------|--|
| VANTEET | Giant S-X2 Disc wheelset, alloy |
| NAVAT | Giant alloy, 12mm thru-axle |
| PINNAT | stainless |
| RENKAAT | Giant CrossCut AT 2, 700x38c, tubeless |
| LISÄTIEDOT | tubeless prepared, 53mm max tire size in "long" flip chip position, 45mm max tire size in "short" flip chip position |
| RAJOITTEET | |
| MAX RENGASVARA | 53mm |

Suositusuhinta: 1 809,00 €

GEOMETRIA

| RUNKO | M | | ML | |
|------------------------------------|-------------|-------------|-------|------|
| | SHORT | LONG | SHORT | LONG |
| Satulaputken pituus (mm) | 470 | 490 | | |
| Satulaputken kulma | 73,5° | 73,0° | | |
| Vaakaputken pituus (mm) | 560 | 575 | | |
| Emäputken pituus (mm) | 150 | 165 | | |
| Emäputken kulma | 71,5° | 72,0° | | |
| Haarukan offset (mm) | 50 | 50 | | |
| Trail-mitta (mm) | 68 72 | 65 68 | | |
| Akseliväli (mm) | 1030 1040 | 1035 1045 | | |
| Takahaarukan alaputken pituus (mm) | 430 440 | 430 440 | | |
| Keskiön pudotus (mm) | 80 81 | 80 81 | | |
| Stack-mitta (mm) | 586 | 602 | | |
| Reach-mitta (mm) | 387 | 391 | | |
| Standover-mitta (mm) | 752 759 | 769 776 | | |
| Ohjaustangon leveys (mm) | 440 | 440 | | |
| Ohjainkannattimen pituus (mm) | 70 | 80 | | |
| Kammen pituus (mm) | 172,5 | 172,5 | | |
| Rengaskoko | 700x 42C | 700x 42C | | |

Kaikki ilmoitetut tekniset tiedot voivat muuttua ilman erillistä ilmoitusta.