



SPECS

CADRU	
MARIMI	XS, S, M, M/L, L, XL
CULORI	Alpine Green, Bali Bricks
CADRU	ALUXX-grade aluminum, 12x142mm thru-axle, disc, flip chip dropout
FURCA	Advanced-grade composite, full-composite OverDrive steerer, 12mm thru-axle, disc
COMPONENTE	
GHIDON	Giant Contact XR D-Fuse, 31.8mm XS:42cm, S:42cm, M:44cm, M/L:44cm, L:46cm, XL:46cm
GRIPS	cork tape with gel
PIPA	Giant Contact, 8-degree XS:50mm, S:60mm, M:70mm, M/L:80mm, L:80mm, XL:90mm
TIJA SA	Giant D-Fuse, alloy, 14mm offset
SA	Giant Grit
SISTEMUL DE SCHIMBARE A VITEZELOR	
MANETE SCHIMBATOR	Shimano CUES U6030, 2x10
SCHIMBATOR FATA	Shimano CUES U6030
SCHIMBATOR SPATE	Shimano CUES U6020
FRANE	Shimano CUES U6030 hydraulic, Giant MPH rotors [F]160mm, [R]160mm
MANETE FRANA	Shimano CUES U6030 hydraulic
PINIOANE	Shimano CS-LG300, 11x39
LANT	KMC X11
ANGRENAJ	Shimano FC-U6030-2, 32/46 XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175mm
BOTTOM BRACKET	Shimano, threaded

ROTI	
JANTE	Giant S-X2, alloy
BUTUCI	Giant alloy, 12mm thru-axle
SPITE	stainless
ANVELOPE	CrossCut GRIP 1; 700x45c
EXTRAS	tubeless prepared, 53mm max tire size in "long" flip chip position, 45mm max tire size in "short" flip chip position
LIMITS	
MAX TIRE CLEARANCE	53mm

GEOMETRIE

CADRU	XS		S		M		ML		L		XL	
	LOW	HIGH	LOW	HIGH	LOW	HIGH	LOW	HIGH	LOW	HIGH	LOW	HIGH
Seat Tube Length (mm)	430	450	470	490	510	530	550	570	590	610	630	650
Seat Tube Angle	74,0°	73,5°	73,5°	73,0°	73,0°	73,0°	72,5°	72,5°	72,0°	72,0°	71,5°	71,5°
Top Tube Length (mm)	540	550	560	575	585	600	615	625	640	650	665	675
Head Tube Length (mm)	125	135	150	165	180	195	210	220	235	245	260	270
Head Tube Angle	70,0°	71,0°	71,5°	72,0°	72,0°	72,0°	71,5°	71,5°	71,0°	71,0°	70,5°	70,5°
Fork Rake (mm)	50	50	50	50	50	50	50	50	50	50	50	50
Trail (mm)	78 82	72 75	68 72	65 68	65 68	65 68	65 68	65 68	65 68	65 68	65 68	65 68
Wheelbase (mm)	1029 1039	1025 1035	1030 1040	1035 1045	1045 1055	1061 1071	1066 1076	1071 1081	1081 1091	1091 1101	1101 1111	1111 1121
Chain Stay Length (mm)	430 440	430 440	430 440	430 440	430 440	430 440	430 440	430 440	430 440	430 440	430 440	430 440
Bottom Bracket Drop (mm)	80 81	80 81	80 81	80 81	80 81	80 81	80 81	80 81	80 81	80 81	80 81	80 81
Stack (mm)	556	570	586	602	616	630	646	660	676	690	706	720
Reach (mm)	381	381	387	391	397	407	417	427	437	447	457	467
Stand Over Height (mm)	717 724	734 741	752 759	769 776	786 793	801 810	816 823	831 838	846 853	861 868	876 883	891 898
Handlebar Width (mm)	420	420	440	440	460	460	480	480	500	500	520	520
Stem Length (mm)	50	60	70	80	80	90	100	110	120	130	140	150
Crank Length (mm)	170	170	172,5	172,5	175	175	177,5	177,5	180	180	182,5	182,5
Wheel Size	700x 42C	700x 42C	700x 42C	700x 42C	700x 42C	700x 42C	700x 42C	700x 42C	700x 42C	700x 42C	700x 42C	700x 42C

Toate specificatiile enumerate se pot schimba fara notificare prealabila.