



SPECIFIKACIJE

OKVIR	
VELIKOSTI	XS, S, M, M/L, L, XL
BARVE	Metal/Shoreline, Pale Olive
OKVIR	ALUXX-grade aluminum, 12x142mm thru-axle, disc, flip chip dropout
VILICE	Advanced-grade composite, full-composite OverDrive steerer, 12mm thru-axle, disc
KOMPONENTE	
KRMILO	Giant Contact XR D-Fuse, 31.8mm XS:42cm, S:42cm, M:44cm, M/L:44cm, L:46cm, XL:46cm
GRIPS	cork tape with gel
OPORA KRMILA	Giant Contact, 8-degree XS:50mm, S:60mm, M:70mm, M/L:80mm, L:80mm, XL:90mm
OPORA SEDEŽA	Giant D-Fuse, alloy, 14mm offset
SEDEŽ	Giant Approach
POGON	
PRESTAVNE ROČICE	Shimano GRX RX-400, 2x10
PREDNJI MENJALNIK	Shimano Tiagra
ZADNJI MENJALNIK	Shimano GRX RX-400
ZAVORE	Shimano GRX RX-400 hydraulic, Giant MPH rotors [F]160mm, [R]160mm
ZAVORNE ROČICE	Shimano GRX RX-400 hydraulic
VERIŽNIK	Shimano HG500, 11x34
VERIGA	KMC X10 with Missing Link
GONILKE Z VERIŽNIKI	FSA Omega Adventure, 32/48 XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175mm
BOTTOM BRACKET	FSA Mega EXO

OBROČNIKI	
OBROČI	Giant S-X2 Disc wheelset, alloy
PESTA	Giant alloy, 12mm thru-axle
NAPERE	stainless
PLAŠČI	Giant CrossCut AT 2, 700x38c, tubeless
DODATKI	tubeless prepared, 53mm max tire size in "long" flip chip position, 45mm max tire size in "short" flip chip position
LIMITS	
MAX TIRE CLEARANCE	53mm

GEOMETRIJA

OKVIR	XS		S		M		ML		L	
	LOW	HIGH	LOW	HIGH	LOW	HIGH	LOW	HIGH	LOW	HIGH
Dolžina sedežne cevi (mm)	430		450		470		490		510	
Kot sedežne cevi	74,0°		73,5°		73,5°		73,0°		73,0°	
Top Tube Length (mm)	540		550		560		575		585	
Višina glave okvirja (mm)	125		135		150		165		180	
Krmilni kot	70,0°		71,0°		71,5°		72,0°		72,0°	
Zamik vpetja osi (mm)	50		50		50		50		50	
Trail (mm)	78 82		72 75		68 72		65 68		65 68	
Medosna razdalja (mm)	1029 1039		1025 1035		1030 1040		1035 1045		1045 1055	
Dolžina cevi ob verigi (mm)	430 440		430 440		430 440		430 440		430 440	
Bottom Bracket Drop (mm)	80 81		80 81		80 81		80 81		80 81	
Oddaljenost zgornje cevi od gonilne osi (mm)	556		570		586		602		616	
Doseg (mm)	381		381		387		391		397	
Višina zgornje cevi (mm)	717 724		734 741		752 759		769 776		786 793	
Širina krmila (mm)	420		420		440		440		460	
Dolžina opore krmila (mm)	50		60		70		80		80	
Dolžina gonilke (mm)	170		170		172,5		172,5		175	
Velikost obročnikov	700x 42C		700x 42C		700x 42C		700x 42C		700x 42C	

Vse navedene specifikacije se lahko spremenijo brez obvestila.