



SPECS

FRAME	
SIZES	XS, S, M, M/L, L, XL
COLORS	Ocean Storm, Icicle White
FRAME	ALUXX-grade aluminum, 12x142mm thru-axle, disc, flip chip dropout
FORK	Advanced-grade composite, full-composite OverDrive steerer, 12mm thru-axle, disc
COMPONENTS	
HANDLEBAR	Giant Contact XR Ergo-Control, 31.8mm XS:42cm, S:42cm, M:44cm, M/L:44cm, L:46cm, XL:46cm
GRIPS	cork tape with gel
STEM	Giant Contact, 8-degree XS:50mm, S:60mm, M:70mm, M/L:80mm, L:80mm, XL:90mm
SEATPOST	Giant D-Fuse, alloy, 14mm offset
SADDLE	Giant Grit
DRIVETRAIN	
SHIFTERS	Shimano CUES U3030, 2x9
FRONT DERAILLEUR	Shimano CUES U6030
REAR DERAILLEUR	Shimano CUES U4020
BRAKES	Shimano BR-RS305 mechanical, Giant MPH rotors [F]160mm, [R]160mm
BRAKE LEVERS	Shimano CUES U3030 hydraulic
CASSETTE	Shimano CS-LG300, 11x36
CHAIN	KMC X11
CRANKSET	Shimano FC-U6030-2, 32/46 XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175mm
BOTTOM BRACKET	Shimano, threaded

WHEELS	
RIMS	Giant S-X2, alloy
HUBS	Giant alloy, 12mm thru-axle
SPOKES	stainless
TIRES	CrossCut GRIP 1; 700x45c
EXTRAS	tubeless prepared, 53mm max tire size in "long" flip chip position, 45mm max tire size in "short" flip chip position
LIMITS	
MAX TIRE CLEARANCE	53mm

GEOMETRY

FRAME	XS		S		M		ML		L		XL	
	LOW	HIGH LOW	LOW	HIGH LOW	LOW	HIGH LOW	LOW	HIGH LOW	LOW	HIGH LOW	LOW	HIGH
Seat Tube Length (mm)	430	450	470	490	510	530						
Seat Tube Angle	74,0°	73,5°	73,5°	73,0°	73,0°	73,0°						
Top Tube Length (mm)	540	550	560	575	585	600						
Head Tube Length (mm)	125	135	150	165	180	195						
Head Tube Angle	70,0°	71,0°	71,5°	72,0°	72,0°	72,0°						
Fork Rake (mm)	50	50	50	50	50	50						
Trail (mm)	78 82	72 75	68 72	65 68	65 68	65 68						
Wheelbase (mm)	1029 1039	1025 1035	1030 1040	1035 1045	1045 1055	1061 1071						
Chain Stay Length (mm)	430 440	430 440	430 440	430 440	430 440	430 440						
Bottom Bracket Drop (mm)	80 81	80 81	80 81	80 81	80 81	80 81						
Stack (mm)	556	570	586	602	616	630						
Reach (mm)	381	381	387	391	397	407						
Stand Over Height (mm)	717 724	734 741	752 759	769 776	786 793	801 810						
Handlebar Width (mm)	420	420	440	440	460	460						
Stem Length (mm)	50	60	70	80	80	90						
Crank Length (mm)	170	170	172,5	172,5	175	175						
Wheel Size	700x 42C	700x 42C	700x 42C	700x 42C	700x 42C	700x 42C						

All specifications listed are subject to change without notice.