



SPECS

FRAME	
SIZES	S, M, M/L, L, XL
COLOURS	Gloss Metallic Black/Sea Sparkle & Gloss Bay Leaf/Panther
FRAME	ALUXX-grade aluminium, 12x142mm thru-axle, disc, flip chip dropout
FORK	Advanced-grade composite, full-composite OverDrive steerer, 12mm thru-axle, disc
SHOCK	N/A
COMPONENTS	
HANDLEBAR	Giant Contact XR Ergo-Control, 31.8mm
GRIPS	cork tape with gel
STEM	Giant Sport, 8-degree
SEATPOST	Giant D-Fuse, alloy, 14mm offset
SADDLE	Giant Approach
PEDALS	PEDALS NOT SUPPLIED
DRIVETRAIN	
SHIFTERS	Shimano Sora, 2x9
FRONT DERAILLEUR	Shimano Sora
REAR DERAILLEUR	Shimano Sora, long cage
BRAKES	Tektro MD-C550 mechanical, Giant MPH rotors [F]160mm, [R]160mm
BRAKE LEVERS	Shimano Sora
CASSETTE	Shimano HG400, 11x34
CHAIN	KMC X9 with Missing Link
CRANKSET	FSA Vero Pro, 32/48
BOTTOM BRACKET	cartridge

WHEELS	
RIMS	Giant S-X2 Disc wheelset, alloy, 25mm inner rim width
HUBS	Giant alloy, 12mm thru-axle
SPOKES	Stainless steel
TYRES	Giant CrossCut AT 2, 700x38c, tubeless
EXTRAS	Factory tubeless set up, 53mm max tyre size in "long" flip chip position, 45mm max tyre size in "short" flip chip position
LIMITS	
MAX CHAINRING SIZE	SRAM Wide 2x 43-30, 1x 46T. SRAM Road 2x 52-39, 1x 52T. Shimano Road 2x 52-36. GRX 2x 48-31, 1x 42T

Price: €1,499.00

GEOMETRY

FRAME	S		M		ML		L	
	LOW	HIGH	LOW	HIGH	LOW	HIGH	LOW	HIGH
Seat Tube Length (mm)	450		470		490		510	
Seat Tube Angle	73.5°		73.5°		73.0°		73.0°	
Top Tube Length (mm)	550		560		575		585	
Head Tube Length (mm)	135		150		165		180	
Head Tube Angle	71.0°		71.5°		72.0°		72.0°	
Fork Rake (mm)	50		50		50		50	
Trail (mm)	72 75		68 72		65 68		65 68	
Wheelbase (mm)	1025 1035		1030 1040		1035 1045		1045 1055	
Chain Stay Length (mm)	430 440		430 440		430 440		430 440	
Bottom Bracket Drop (mm)	80 81		80 81		80 81		80 81	
Stack (mm)	570		586		602		616	
Reach (mm)	381		387		391		397	
Stand Over Height (mm)	734 741		752 759		769 776		786 793	
Handlebar Width (mm)	420		440		440		460	
Stem Length (mm)	60		70		80		80	
Crank Length (mm)	170		172.5		172.5		175	
Wheel Size	700x 42C		700x 42C		700x 42C		700x 42C	

All specifications listed are subject to change without notice.