



## SPECS

FRAME	
<b>SIZES</b>	XS, S, M, M/L, L, XL
<b>COLORS</b>	Metallic Black, Bay Leaf
<b>FRAME</b>	ALUXX-grade aluminum, 12x142mm thru-axle, disc, flip chip dropout
<b>FORK</b>	Advanced-grade composite, full-composite OverDrive steerer, 12mm thru-axle, disc
<b>SHOCK</b>	N/A
COMPONENTS	
<b>HANDLEBAR</b>	Giant Contact XR Ergo-Control, 31.8mm XS:42cm, S:42cm, M:44cm, M/L:44cm, L:46cm, XL:46cm
<b>GRIPS</b>	cork tape with gel
<b>STEM</b>	Giant Sport, 8-degree XS:50mm, S:60mm, M:70mm, M/L:80mm, L:80mm, XL:90mm
<b>SEATPOST</b>	Giant D-Fuse, alloy, 14mm offset
<b>SADDLE</b>	Giant Approach
<b>PEDALS</b>	N/A
DRIVETRAIN	
<b>SHIFTERS</b>	Shimano Sora, 2x9
<b>FRONT DERAILLEUR</b>	Shimano Sora
<b>REAR DERAILLEUR</b>	Shimano Sora, long cage
<b>BRAKES</b>	Tektro MD-C550 mechanical, Giant MPH rotors [F]160mm, [R]160mm
<b>BRAKE LEVERS</b>	Shimano Sora
<b>CASSETTE</b>	Shimano HG400, 11x34
<b>CHAIN</b>	KMC X9 with Missing Link
<b>CRANKSET</b>	FSA Vero Pro, 32/48 XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175mm
<b>BOTTOM BRACKET</b>	cartridge

WHEELS	
<b>RIMS</b>	Giant S-X2 Disc wheelset, alloy
<b>HUBS</b>	Giant alloy, 12mm thru-axle
<b>SPOKES</b>	stainless
<b>TIRES</b>	Giant CrossCut AT 2, 700x38c, tubeless
<b>EXTRAS</b>	tubeless prepared, 53mm max tire size in "long" flip chip position, 45mm max tire size in "short" flip chip position

**Price: \$2,299.00**

## GEOMETRY

FRAME	XS	S	M	ML	L	XL
	SHORT   LONG SHORT	LONG SHORT	LONG SHORT	LONG SHORT	LONG SHORT	LONG SHORT
Seat Tube Length (mm)	430	450	470	490	510	530
Seat Tube Angle	74.0°	73.5°	73.5°	73.0°	73.0°	73.0°
Top Tube Length (mm)	540	550	560	575	585	600
Head Tube Length (mm)	125	135	150	165	180	195
Head Tube Angle	70.0°	71.0°	71.5°	72.0°	72.0°	72.0°
Fork Rake (mm)	50	50	50	50	50	50
Trail (mm)	78   82	72   75	68   72	65   68	65   68	65
Wheelbase (mm)	1029   1039	1025   1035	1030   1040	1035   1045	1045   1055	1060
Chain Stay Length (mm)	430   440	430   440	430   440	430   440	430   440	430
Bottom Bracket Drop (mm)	80   81	80   81	80   81	80   81	80   81	80
Stack (mm)	556	570	586	602	616	630
Reach (mm)	381	381	387	391	397	407
Stand Over Height (mm)	717   724	734   741	752   759	769   776	786   793	807
Stem Length (mm)	50	60	70	80	80	90
Crank Length (mm)	170	170	172.5	172.5	175	175
Wheel Size	700x 42C	700x 42C	700x 42C	700x 42C	700x 42C	700x 42C

Please note that our specifications may be impacted by running substitution changes, we highly recommend confirming the specifications of our products with your local retailer at the time of sale if purchasing in-store. \*Recommended Retail Prices are subject to change without notice and may vary from store to store depending on freight and assembly costs.