

REVOLT 2



SPECS

| FRAME | |
|-------------------------|--|
| SIZES | XS, S, M, M/L, L, XL |
| COLOURS | Asphalt Green, Storm Cloud |
| FRAME | ALUXX-grade aluminum, 12x142mm thru-axle, disc, flip chip dropout |
| FORK | Advanced-grade composite, full-composite OverDrive steerer, 12mm thru-axle, disc |
| COMPONENTS | |
| HANDLEBAR | Giant Contact XR Ergo-Control, 31.8mm XS:42cm, S:42cm, M:44cm, M/L:44cm, L:46cm, XL:46cm |
| GRIPS | cork tape with gel |
| STEM | Giant Sport, 8-degree XS:50mm, S:60mm, M:70mm, M/L:80mm, L:80mm, XL:90mm |
| SEATPOST | Giant D-Fuse, alloy, 14mm offset |
| SADDLE | Giant Approach |
| DRIVETRAIN | |
| SHIFTERS | Shimano Sora, 2x9 |
| FRONT DERAILLEUR | Shimano Sora |
| REAR DERAILLEUR | Shimano Sora, long cage |
| BRAKES | Tektro MD-C550 mechanical, Giant MPH rotors [F]160mm, [R]160mm |
| BRAKE LEVERS | Shimano Sora |
| CASSETTE | Shimano HG400, 11x34 |
| CHAIN | KMC X9 with Missing Link |
| CRANKSET | FSA Vero Pro, 32/48 XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175mm |
| BOTTOM BRACKET | cartridge |

| WHEELS | |
|---------------------------|--|
| RIMS | Giant S-X2 Disc wheelset, alloy |
| HUBS | Giant alloy, 12mm thru-axle |
| SPOKES | stainless |
| TIRES | Giant CrossCut AT 2, 700x38c, tubeless |
| EXTRAS | tubeless prepared, 53mm max tire size in "long" flip chip position, 45mm max tire size in "short" flip chip position |
| LIMITS | |
| MAX TIRE CLEARANCE | 53mm |

Suggested Retail Price (CDN): \$1,699.00

FRAME GEOMETRY

| FRAME | XS | S | M | ML | L | XL |
|--------------------------|-------------|-------------|-------------|-------------|-------------|----------|
| | SHORT | LONG SHORT | LONG SHORT | LONG SHORT | LONG SHORT | LONG SH |
| Seat Tube Length (mm) | 430 | 450 | 470 | 490 | 510 | 530 |
| Seat Tube Angle | 74.0° | 73.5° | 73.5° | 73.0° | 73.0° | 73.0° |
| Top Tube Length (mm) | 540 | 550 | 560 | 575 | 585 | 600 |
| Head Tube Length (mm) | 125 | 135 | 150 | 165 | 180 | 190 |
| Head Tube Angle | 70.0° | 71.0° | 71.5° | 72.0° | 72.0° | 72.0° |
| Fork Rake (mm) | 50 | 50 | 50 | 50 | 50 | 50 |
| Trail (mm) | 78 82 | 72 75 | 68 72 | 65 68 | 65 68 | 65 |
| Wheelbase (mm) | 1029 1039 | 1025 1035 | 1030 1040 | 1035 1045 | 1045 1055 | 1045 |
| Chain Stay Length (mm) | 430 440 | 430 440 | 430 440 | 430 440 | 430 440 | 430 |
| Bottom Bracket Drop (mm) | 80 81 | 80 81 | 80 81 | 80 81 | 80 81 | 80 |
| Stack (mm) | 556 | 570 | 586 | 602 | 616 | 630 |
| Reach (mm) | 381 | 381 | 387 | 391 | 397 | 400 |
| Stand Over Height (mm) | 717 724 | 734 741 | 752 759 | 769 776 | 786 793 | 800 |
| Handlebar Width (mm) | 420 | 420 | 440 | 440 | 460 | 460 |
| Stem Length (mm) | 50 | 60 | 70 | 80 | 80 | 90 |
| Crank Length (mm) | 170 | 170 | 172.5 | 172.5 | 175 | 175 |
| Wheel Size | 700x 42C | 700x 42C | 700x 42C | 700x 42C | 700x 42C | 700x 42C |

All prices and specifications are subject to change without notice.