



TECHNIQUES

CADRE	
TAILLES	XS, S, M, M/L, L, XL
COLORIS	Bay Leaf
CADRE	ALUXX-grade aluminum, 12x142mm thru-axle, disc, flip chip dropout
FOURCHE	Advanced-grade composite, full-composite OverDrive steerer, 12mm thru-axle, disc
AMORTISSEUR	N/A
COMPOSANTS	
CINTRE	Giant Contact XR Ergo-Control, 31.8mm XS:42cm, S:42cm, M:44cm, M/L:44cm, L:46cm, XL:46cm
POIGNÉES	cork tape with gel
POTENCE	Giant Sport, 8-degree XS:50mm, S:60mm, M:70mm, M/L:80mm, L:80mm, XL:90mm
TIGE DE SELLE	Giant D-Fuse, alloy, 14mm offset
SELLE	Giant Approach
PÉDALES	N/A
DÉRAILLEUR	
MANETTES	Shimano Sora, 2x9
DÉRAILLEUR AVANT	Shimano Sora
DÉRAILLEUR ARRIÈRE	Shimano Sora, long cage
FREINS	Tektro MD-C550 mechanical, Giant MPH rotors [F]160mm, [R]160mm
LEVIER DE FREIN	Shimano Sora
CASSETTE	Shimano HG400, 11x34
CHAÎNE	KMC X9 with Missing Link
PÉDALIER	FSA Vero Pro, 32/48 XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175mm
BOITIER DE PÉDALIER	cartridge

ROUES	
JANTES	Giant S-X2 Disc wheelset, alloy
MOYEUX	Giant alloy, 12mm thru-axle
RAYONS	stainless
PNEUS	Giant CrossCut AT 2, 700x38c, tubeless
EXTRAS	tubeless prepared, 53mm max tire size in "long" flip chip position, 45mm max tire size in "short" flip chip position
ACCESSOIRES	
ECLAIRAGE	Kit d'éclairage avant et arrière à piles

Prix Public Conseillé: 1 550,00 €

GÉOMÉTRIE

CADRE	XS		S		M		ML		L		XL	
	LOW	HIGH	LOW	HIGH	LOW	HIGH	LOW	HIGH	LOW	HIGH	LOW	HIGH
Longueur de tube de selle (mm)	430		450		470		490		510		530	
Angle de tube de selle	74,0°		73,5°		73,5°		73,0°		73,0°		73,0°	
Longueur du tube supérieur (mm)	540		550		560		575		585		600	
Longueur du tube de direction (mm)	125		135		150		165		180		195	
Angle du tube de direction	70,0°		71,0°		71,5°		72,0°		72,0°		72,0°	
Déport de fourche (mm)	50		50		50		50		50		50	
Trail (mm)	78 82		72 75		68 72		65 68		65 68		65 68	
Empattement (mm)	1029 1039		1025 1035		1030 1040		1035 1045		1045 1055		1061 1071	
Longueur des bases (mm)	430 440		430 440		430 440		430 440		430 440		430 440	
Drop du boîtier de pédalier (mm)	80 81		80 81		80 81		80 81		80 81		80 81	
Stack (mm)	556		570		586		602		616		630	
Reach (mm)	381		381		387		391		397		407	
Hauteur en statique (mm)	717 724		734 741		752 759		769 776		786 793		801 808	
Largeur de cintre (mm)	420		420		440		440		460		460	
Longueur de potence (mm)	50		60		70		80		80		90	
Longueur des manivelles (mm)	170		170		172,5		172,5		175		175	
Diamètre des roues	700x 42C		700x 42C		700x 42C		700x 42C		700x 42C		700x 42C	

Produits conformes aux exigences de sécurité (décret n° 2016-364 du 29 mars 2016).
GIANT France se réserve le droit de modifier les spécifications sans préavis.