



SPECIFIKACIJE

OKVIR	
VELIKOSTI	XS, S, M, M/L, L, XL
BARVE	Asphalt Green, Storm Cloud
OKVIR	ALUXX-grade aluminum, 12x142mm thru-axle, disc, flip chip dropout
VILICE	Advanced-grade composite, full-composite OverDrive steerer, 12mm thru-axle, disc
KOMPONENTE	
KRMILO	Giant Contact XR Ergo-Control, 31.8mm XS:42cm, S:42cm, M:44cm, M/L:44cm, L:46cm, XL:46cm
GRIPS	cork tape with gel
OPORA KRMILA	Giant Sport, 8-degree XS:50mm, S:60mm, M:70mm, M/L:80mm, L:80mm, XL:90mm
OPORA SEDEŽA	Giant D-Fuse, alloy, 14mm offset
SEDEŽ	Giant Approach
POGON	
PRESTAVNE ROČICE	Shimano Sora, 2x9
PREDNJI MENJALNIK	Shimano Sora
ZADNJI MENJALNIK	Shimano Sora, long cage
ZAVORE	Tektro MD-C550 mechanical, Giant MPH rotors [F]160mm, [R]160mm
ZAVORNE ROČICE	Shimano Sora
VERIŽNIK	Shimano HG400, 11x34
VERIGA	KMC X9 with Missing Link
GONILKE Z VERIŽNIKI	FSA Vero Pro, 32/48 XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175mm
BOTTOM BRACKET	cartridge

OBROČNIKI	
OBROČI	Giant S-X2 Disc wheelset, alloy
PESTA	Giant alloy, 12mm thru-axle
NAPERE	stainless
PLAŠČI	Giant CrossCut AT 2, 700x38c, tubeless
DODATKI	tubeless prepared, 53mm max tire size in "long" flip chip position, 45mm max tire size in "short" flip chip position
LIMITS	
MAX TIRE CLEARANCE	53mm

GEOMETRIJA

OKVIR	XS		S		M		ML		L
	SHORT	LONG	SHORT	LONG	SHORT	LONG	SHORT	LONG	
Dolžina sedežne cevi (mm)	430	450	450	470	470	490	490	510	530
Kot sedežne cevi	74,0°	73,5°	73,5°	73,5°	73,5°	73,0°	73,0°	73,0°	73,0°
Top Tube Length (mm)	540	550	550	560	560	575	575	590	600
Višina glave okvirja (mm)	125	135	135	150	150	165	165	180	190
Krmilni kot	70,0°	71,0°	71,0°	71,5°	71,5°	72,0°	72,0°	72,0°	72,0°
Zamik vpetja osi (mm)	50	50	50	50	50	50	50	50	50
Trail (mm)	78 82	72 75	72 75	68 72	68 72	65 68	65 68	62 65	60 63
Medosna razdalja (mm)	1029 1039	1025 1035	1025 1035	1030 1040	1030 1040	1035 1045	1035 1045	1040 1050	1045 1055
Dolžina cevi ob verigi (mm)	430 440	430 440	430 440	430 440	430 440	430 440	430 440	430 440	430 440
Bottom Bracket Drop (mm)	80 81	80 81	80 81	80 81	80 81	80 81	80 81	80 81	80 81
Oddaljenost zgornje cevi od gonilne osi (mm)	556	570	570	586	586	602	602	618	634
Doseg (mm)	381	381	381	387	387	391	391	397	403
Višina zgornje cevi (mm)	717 724	734 741	734 741	752 759	752 759	769 776	769 776	787 794	804 811
Širina krmila (mm)	420	420	420	440	440	440	440	460	460
Dolžina opore krmila (mm)	50	60	60	70	70	80	80	90	90
Dolžina gonilke (mm)	170	170	170	172,5	172,5	172,5	172,5	175	175
Velikost obročnikov	700x 42C	700x 42C	700x 42C	700x 42C	700x 42C	700x 42C	700x 42C	700x 42C	700x 42C

Vse navedene specifikacije se lahko spremenijo brez obvestila.