



СПЕЦИФИКАЦИИ

РАМКА	
РАЗМЕР	XS, S, M, M/L, L, XL
ЦВЯТ	Prismatic Haze / Aurora Noise
РАМКА	Advanced-grade composite, 12x142mm thru-axle, disc, flip chip dropout, down tube storage
ВИЛКА	Advanced-grade composite, full-composite OverDrive steerer, 12mm thru-axle, disc
КОМПОНЕНТИ	
КОРМИЛО	Giant Contact XR D-Fuse, 31.8mm XS:42cm, S:42cm, M:44cm, M/L:44cm, L:46cm, XL:46cm
ГРИПОВЕ	Stratus Lite 3.0
ЛАПА	Giant Contact AeroLight, -10 degree XS:50mm, S:60mm, M:70mm, M/L:80mm, L:80mm, XL:90mm
КОЛЧЕ ЗА СЕДАЛКА	Giant D-Fuse SL, composite, -5/+15mm offset
СЕДАЛКА	Giant Grit
DRIVETRAIN	
КОМАНДИ	Shimano GRX RX-820, 2x12
ПРЕДЕН ДЕРАЙЛЪОР	Shimano GRX RX-820
ЗАДЕН ДЕРАЙЛЪОР	Shimano GRX RX-820
СПИРАЧКИ	Shimano GRX RX-820 hydraulic, Shimano SM-RT70 rotors [F]160mm, [R]160mm
РЪКОХВАТКИ ЗА СПИРАЧКИ	Shimano GRX RX-820 hydraulic
КАСЕТА	Shimano CS-HG710, 12-speed, 11x36
ВЕРИГА	KMC X12L-1
КУРБЕЛ	Shimano GRX RX-820, 31/48 XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175mm
СРЕДНА КАСЕТА	Shimano, press fit

КАПЛИ	
ШИНИ	Giant CXR 2 Carbon Disc WheelSystem, [F] 35mm, [R] 35mm
ГЛАВИНИ	[F] Giant alloy, CenterLock, 12mm thru-axle [R] Giant alloy, 3-pawl 36t driver, CenterLock, 12mm thru-axle
СПИЦИ	Sapim Sprint
ГУМИ	CADEX GX, 700x40c, tubeless
ЕКСТРИ	tubeless prepared, 53mm max tire size in "long" flip chip position, 53mm max tire size in "short" flip chip position, in-frame storage bag
ЛИМИТИ	
MAX TIRE CLEARANCE	53mm

ГЕОМЕТРИЯ

РАМКА	XS	S	M	ML	L	XL
	SHORT LONG SHORT	LONG SHORT LONG SHORT	LONG SHORT LONG SHORT	LONG SHORT LONG SHORT	LONG SHORT LONG SHORT	LONG SHORT LONG SHORT
Seat Tube Length (mm)	430	450	470	490	510	530
Seat Tube Angle	74,0°	73,5°	73,5°	73,0°	73,0°	73,0°
Top Tube Length (mm)	540	550	560	575	585	600
Head Tube Length (mm)	125	135	150	165	180	190
Head Tube Angle	70,0°	71,0°	71,5°	72,0°	72,0°	72,0°
Fork Rake (mm)	50	50	50	50	50	50
Trail (mm)	78 82	72 75	68 72	65 68	65 68	65 68
Wheelbase (mm)	1024 1034	1020 1030	1026 1036	1031 1041	1041 1051	1041 1051
Chain Stay Length (mm)	425 435	425 435	425 435	425 435	425 435	425 435
Bottom Bracket Drop (mm)	80 81	80 81	80 81	80 81	80 81	80 81
Stack (mm)	556	570	586	602	616	630
Обсер (mm)	381	381	387	391	397	401
Stand Over Height (mm)	724 731	740 747	757 764	774 780	791 797	800 806
Ширина на Кормило (mm)	420	420	440	440	460	460
Дължина на Лапа (mm)	50	60	70	80	80	90
Дължина на Курбел (mm)	170	170	172,5	172,5	175	175
Размер на Каплите	700c	700c	700c	700c	700c	700c

All specifications listed are subject to change without notice.