

REVOLT ADVANCED 0



SPECIFIKATIONER

RAMME	
STØRRELSER	S, M, M/L, L, XL
FARVER	Snow Drift
RAMME	Advanced-grade composite, 12x142mm thru-axle, disc, flip chip dropout, down tube storage
FORGAFFEL	Advanced-grade composite, full-composite OverDrive steerer, 12mm thru-axle, disc
KOMPONENTER	
STYR	Giant Contact XR D-Fuse, 31.8mm XS:42cm, S:42cm, M:44cm, M/L:44cm, L:46cm, XL:46cm
GREB / STYRBÅND	Stratus Lite 3.0
FREMPIND	Giant Contact AeroLight, -10 degree XS:50mm, S:60mm, M:70mm, M/L:80mm, L:80mm, XL:90mm
SADELPIND	Giant D-Fuse SL, composite, -5/+15mm offset
SADEL	Giant Grit
PEDALER	no pedal [GA, Pan-Eu], platform pedal [GU, GV, GJ]
GEARGRUPPE	
SKIFTEGREB	Shimano GRX RX-820, 2x12
FORSKIFTER	Shimano GRX RX-820
BAGSKIFTER	Shimano GRX RX-820
BREMSE	Shimano GRX RX-820 hydraulic, Shimano SM-RT70 rotors [F]160mm, [R]160mm
BREMSEGREB	Shimano GRX RX-820 hydraulic
KASSETTE	Shimano CS-HG710, 12-speed, 11x36
KÆDE	KMC X12L-1
KRANKSÆT	Shimano GRX RX-820, 31/48 XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175mm
KRANKBOKS	Shimano, press fit

HJUL	
FÆLGE	Giant CXR 2 WheelSystem, [F] 35mm, [R] 35mm
NAV	[F] Giant alloy, CenterLock, 12mm thru-axle, [R] Giant alloy, 3-pawl 36t driver, CenterLock, 12mm thru-axle
EGER	Sapim Sprint
DÆK	Crosscut Grip 45c
EKSTRA	tubeless prepared, 53mm max tire size in "long" flip chip position, 45mm max tire size in "short" flip chip position, in-frame storage bag
GRÆNSER	
MAX DÆKSTØRRELSE	53mm

Pris: 34.399,00 kr.

GEOMETRI

RAMME	S	M	ML	L	XL
	SHORT LONG	SHORT LONG	SHORT LONG	SHORT LONG	SHORT LONG
Sadelrørslængde (mm)	450	470	490	510	530
Sadelpindindsætningsdybde (mm)	308	323	363	375	375
Sadelrørsvinkel	73,5°	73,5°	73,0°	73,0°	73,0°
Overrørslængde (mm)	550	560	575	585	600
Kronrørslængde (mm)	135	150	165	180	195
Kronrørsvinkel	71,0°	71,5°	72,0°	72,0°	72,0°
Forgaffel fremspring (rake) (mm)	50	50	50	50	50
Sti (mm)	72 75	68 72	65 68	65 68	65 68
Akselafstand (mm)	1020 1030	1026 1036	1031 1041	1041 1051	1056 1066
Kædestagslængde (mm)	425 435	425 435	425 435	425 435	425 435
Krankboks drop (mm)	80 81	80 81	80 81	80 81	80 81
Stack (mm)	570	586	602	616	630
Reach (mm)	381	387	391	397	407
Skridthøjde (mm)	740 747	757 764	774 780	791 797	807 814
Styrbredde (mm)	420	440	440	460	460
Frempindslængde (mm)	60	70	80	80	90
Pedalarmslængde (mm)	170	172,5	172,5	175	175

Alle de anførte specifikationer kan ændres uden varsel.