

# REVOLT ADVANCED 0



## SPECS

FRAME	
<b>SIZES</b>	XS, S, M, M/L, L, XL
<b>COLOURS</b>	Prismatic Haze / Aurora Noise
<b>FRAME</b>	Advanced-grade composite, 12x142mm thru-axle, disc, flip chip dropout, down tube storage
<b>FORK</b>	Advanced-grade composite, full-composite OverDrive steerer, 12mm thru-axle, disc, flat mount disc
COMPONENTS	
<b>HANDLEBAR</b>	Giant Contact XR D-Fuse, 31.8mm XS, S:42cm, M, M/L:44cm, L, XL:46cm
<b>GRIPS</b>	Stratus Lite 3.0
<b>STEM</b>	Giant Contact AeroLight, -10 degree
<b>SEATPOST</b>	Giant D-Fuse SL, composite, -5/+15mm offset
<b>SADDLE</b>	Giant Grit *some bikes may be substituted: Giant Approach
DRIVETRAIN	
<b>SHIFTERS</b>	Shimano GRX RX820, 2x12
<b>FRONT DERAILLEUR</b>	Shimano GRX RX820
<b>REAR DERAILLEUR</b>	Shimano GRX RX820
<b>BRAKES</b>	Shimano GRX RX820 hydraulic, Shimano RT70 rotors [F]160mm, [R]160mm
<b>BRAKE LEVERS</b>	Shimano GRX RX820
<b>CASSETTE</b>	Shimano CS-HG710, 12-speed, 11x36
<b>CHAIN</b>	KMC X12L-1
<b>CRANKSET</b>	Shimano GRX RX820, 31/48 XS, S:170mm, M, M/L:172.5mm, L, XL:175mm
<b>BOTTOM BRACKET</b>	Shimano BB71, press fit

WHEELS	
<b>RIMS</b>	Giant CXR 2 Carbon Disc WheelSystem, 35mm depth, 25mm inner width
<b>HUBS</b>	[F] Giant alloy, CenterLock, 12mm thru-axle [R] Giant alloy, 3-pawl 36t driver, CenterLock, 12mm thru-axle
<b>SPOKES</b>	Sapim Sprint
<b>TIRES</b>	CADEX GX, tubeless, 700x40c, 170 tpi, FOLDING
<b>EXTRAS</b>	tubeless prepared, 53mm max tire size in "long" flip chip position, 45mm max tire size in "short" flip chip position, integrated down tube storage bag
LIMITS	
<b>MAX TIRE CLEARANCE</b>	53mm

**Suggested Retail Price (CDN): \$4,999.00**

## FRAME GEOMETRY

FRAME	XS	S	M	ML	L	XL
	SHORT	LONG SHORT	LONG SHORT	LONG SHORT	LONG SHORT	LONG SH
Seat Tube Length (mm)	430	450	470	490	510	530
Seat Tube Angle	74.0°	73.5°	73.5°	73.0°	73.0°	73.0°
Top Tube Length (mm)	540	550	560	575	585	600
Head Tube Length (mm)	125	135	150	165	180	190
Head Tube Angle	70.0°	71.0°	71.5°	72.0°	72.0°	72.0°
Fork Rake (mm)	50	50	50	50	50	50
Trail (mm)	78   82	72   75	68   72	65   68	65   68	65
Wheelbase (mm)	1024   1034	1020   1030	1026   1036	1031   1041	1041   1051	1051
Chain Stay Length (mm)	425   435	425   435	425   435	425   435	425   435	425
Bottom Bracket Drop (mm)	80   81	80   81	80   81	80   81	80   81	80
Stack (mm)	556	570	586	602	616	630
Reach (mm)	381	381	387	391	397	400
Stand Over Height (mm)	724   731	740   747	757   764	774   780	791   797	800
Handlebar Width (mm)	420	420	440	440	460	460
Stem Length (mm)	50	60	70	80	80	90
Crank Length (mm)	170	170	172.5	172.5	175	175
Wheel Size	700c	700c	700c	700c	700c	700c

*All prices and specifications are subject to change without notice.*