

REVOLT ADVANCED 0

GIANT



ESPECIFICACIONES

CUADRO	
TALLAS	XS, S, M, M/L, L, XL
COLORES	Snow Drift
CUADRO	Advanced-grade composite, 12x142mm thru-axle, disc, flip chip dropout, down tube storage
HORQUILLA	Advanced-grade composite, full-composite OverDrive steerer, 12mm thru-axle, disc
COMPONENTES	
MANILLAR	Giant Contact XR D-Fuse, 31.8mm XS:42cm, S:42cm, M:44cm, M/L:44cm, L:46cm, XL:46cm
PUÑOS	Stratus Lite 3.0
POTENCIA	Giant Contact AeroLight, -10 degree XS:50mm, S:60mm, M:70mm, M/L:80mm, L:80mm, XL:90mm
TIJA DE SILLÍN	Giant D-Fuse SL, composite, -5/+15mm offset
SILLÍN	Giant Grit
PEDALES	no pedal [GA, Pan-Eu], platform pedal [GU, GV, GJ]
TRANSMISIÓN	
MANETAS DE CAMBIO	Shimano GRX RX-820, 2x12
DESVIADOR	Shimano GRX RX-820
CAMBIO TRASERO	Shimano GRX RX-820
FRENOS	Shimano GRX RX-820 hydraulic, Shimano SM-RT70 rotors [F]160mm, [R]160mm
PALANCAS DE FRENOS	Shimano GRX RX-820 hydraulic
CASETTE	Shimano CS-HG710, 12-speed, 11x36
CADENA	KMC X12L-1
JGO. PLATOS Y BIELAS	Shimano GRX RX-820, 31/48 XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175mm
CAJA DE PEDALIER	Shimano, press fit

RUEDAS	
LLANTAS	Giant CXR 2 WheelSystem, [F] 35mm, [R] 35mm
BUJES	[F] Giant alloy, CenterLock, 12mm thru-axle, [R] Giant alloy, 3-pawl 36t driver, CenterLock, 12mm thru-axle
RADIOS	Sapim Sprint
CUBIERTAS	Crosscut Grip 45c
EXTRAS	tubeless prepared, 53mm max tire size in "long" flip chip position, 45mm max tire size in "short" flip chip position, in-frame storage bag
LÍMITES	
MÁXIMA ANCHURA DE NEUMÁTICO	53mm

Precio: 4.299,00 €

GEOMETRÍA

CUADRO	XS	S	M	ML	L
	SHORT LONG	SHORT LONG	SHORT LONG	SHORT LONG	SHORT LONG
Longitud del tubo del sillín (mm)	430	450	470	490	510
Seat Post Insertion Depth (mm)	294	308	323	363	375
Ángulo del tubo del sillín	74,0°	73,5°	73,5°	73,0°	73,0
Longitud del tubo superior (mm) (mm)	540	550	560	575	585
Longitud del tubo de dirección (mm) (mm)	125	135	150	165	180
Ángulo del tubo de dirección	70,0°	71,0°	71,5°	72,0°	72,0
Inclinación de la horquilla (mm)	50	50	50	50	50
Trail (mm) (mm)	78 82	72 75	68 72	65 68	65
Distancia entre ejes (mm) (mm)	1024 1034	1020 1030	1026 1036	1031 1041	104
Longitud de la vaina (mm) (mm)	425 435	425 435	425 435	425 435	425
Caída del eje de pedalier (mm) (mm)	80 81	80 81	80 81	80 81	80
Stack (mm) (mm)	556	570	586	602	616
Reach (mm) (mm)	381	381	387	391	397
Altura del suelo al tubo (mm) (mm)	724 731	740 747	757 764	774 780	791
Ancho del manillar (mm) (mm)	420	420	440	440	460
Longitud de la potencia (mm) (mm)	50	60	70	80	80
Longitud de las bielas (mm) (mm)	170	170	172,5	172,5	175

Giant se reserva el derecho a modificar especificaciones, precios o colores sin previo aviso.