

REVOLT ADVANCED 0

GIANT



ESPECIFICACIONES

CUADRO	
TALLAS	XS, S, M, M/L, L, XL
COLORES	Trekking Green, Carbon
CUADRO	Advanced-grade composite, 12x142mm thru-axle, disc, flip chip dropout
TIJERA	Advanced-grade composite, full-composite OverDrive steerer, 12mm thru-axle, disc
AMORTIGUADOR	N/A
COMPONENTES	
MANUBRIO	Giant Contact XR D-Fuse, 31.8mm XS:42cm, S:42cm, M:44cm, M/L:44cm, L:46cm, XL:46cm
GRIPS	Stratus Lite 3.0
POTENCIA	Giant Contact, 8-degree XS:50mm, S:60mm, M:70mm, M/L:80mm, L:80mm, XL:90mm
POSTE DE ASIENTO	Giant D-Fuse SL, composite, 14mm offset
ASIENTO	Giant Approach
PEDALES	no pedal [GA, Pan-Eu] platform pedal [GU, GV, GJ] pedal w/toeclip and strap [All other GSC]
TRANSMISIÓN	
MANETAS DE CAMBIO	Shimano GRX RX-820, 2x12
DESVIADOR	Shimano GRX RX-820
CAMBIO TRASERO	Shimano GRX RX-820
FRENOS	Shimano GRX RX-820 hydraulic, Shimano SM-RT70 rotors [F]160mm, [R]160mm
PALANCAS DE FRENOS	Shimano GRX RX-820 hydraulic
CASSETTE	Shimano CS-HG710, 12-speed, 11x36
CADENA	KMC X12L-1
MULTIPLICACIÓN	Shimano GRX RX-820, 31/48 XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175mm
EJE DE CENTRO	Shimano, press fit

RUEDAS	
RUEDAS	Giant CXR 2 Carbon Disc WheelSystem, [F] 35mm, [R] 35mm
MAZAS	[F] Giant alloy, CenterLock, 12mm thru-axle, [R] Giant alloy, 3-pawl 36t driver, CenterLock, 12mm thru-axle
RAYOS	Sapim Sprint
NEUMÁTICOS	CADEX AR, 700x40c, tubeless
EXTRAS	tubeless prepared, 53mm max tire size in "long" flip chip position, 45mm max tire size in "short" flip chip position

Precio: \$95,990.00

GEOMETRÍA

CUADRO	XS		S		M		ML		L	
	LOW	HIGH LOW	LOW	HIGH LOW	LOW	HIGH LOW	LOW	HIGH LOW	LOW	HIGH
Longitud de la Base del Poste de Asiento (mm)	430		450		470		490		510	
Ángulo de la Base del Poste de Asiento	74.0°		73.5°		73.5°		73.0°		73.0°	
Longitud del Tubo Superior (mm)	540		550		560		575		585	
Longitud del Telescopio (mm)	125		135		150		165		180	
Ángulo del Telescopio	70.0°		71.0°		71.5°		72.0°		72.0°	
Rake (mm)	50		50		50		50		50	
Trail (mm)	78 82		72 75		68 72		65 68		65 68	
Distancia entre Ejes (mm)	1024 1034		1020 1030		1026 1036		1031 1041		1041 105	
Longitud de Vaina Inferior (mm)	425 435		425 435		425 435		425 435		425 435	
Caída del Eje de Centro (mm)	80 81		80 81		80 81		80 81		80 81	
Stack (mm)	556		570		586		602		616	
Reach (mm)	381		381		387		391		397	
Altura del Tubo Superior al Suelo (mm)	724 731		740 747		757 764		774 780		791 797	
Ancho del Manubrio (mm)	420		420		440		440		460	
Longitud de la Potencia (mm)	50		60		70		80		80	
Longitud de la Biela (mm)	170		170		172.5		172.5		175	
Tamaño de las Ruedas	700C		700C		700C		700C		700C	

Todas las especificaciones están sujetas a cambios sin previo aviso.