

REVOLT ADVANCED 0

GIANT



ESPECIFICACIONES

CUADRO	
TALLAS	XS, S, M, M/L, L, XL
COLORES	Snow Drift
CUADRO	Advanced-grade composite, 12x142mm thru-axle, disc, flip chip dropout, down tube storage
TIJERA	Advanced-grade composite, full-composite OverDrive steerer, 12mm thru-axle, disc
COMPONENTES	
MANUBRIO	Giant Contact XR D-Fuse, 31.8mm XS:42cm, S:42cm, M:44cm, M/L:44cm, L:46cm, XL:46cm
GRIPS	Stratus Lite 3.0
POTENCIA	Giant Contact AeroLight, -10 degree XS:50mm, S:60mm, M:70mm, M/L:80mm, L:80mm, XL:90mm
POSTE DE ASIENTO	Giant D-Fuse SL, composite, -5/+15mm offset
ASIENTO	Giant Grit
PEDALES	no pedal [GA, Pan-Eu], platform pedal [GU, GV, GJ]
TRANSMISIÓN	
MANETAS DE CAMBIO	Shimano GRX RX-820, 2x12
DESVIADOR	Shimano GRX RX-820
CAMBIO TRASERO	Shimano GRX RX-820
FRENOS	Shimano GRX RX-820 hydraulic, Shimano SM-RT70 rotors [F]160mm, [R]160mm
PALANCAS DE FRENOS	Shimano GRX RX-820 hydraulic
CASSETTE	Shimano CS-HG710, 12-speed, 11x36
CADENA	KMC X12L-1
MULTIPLICACIÓN	Shimano GRX RX-820, 31/48 XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175mm
EJE DE CENTRO	Shimano, press fit

RUEDAS	
RUEDAS	Giant CXR 2 WheelSystem, [F] 35mm, [R] 35mm
MAZAS	[F] Giant alloy, CenterLock, 12mm thru-axle, [R] Giant alloy, 3-pawl 36t driver, CenterLock, 12mm thru-axle
RAYOS	Sapim Sprint
NEUMÁTICOS	Crosscut Grip 45c
EXTRAS	tubeless prepared, 53mm max tire size in "long" flip chip position, 45mm max tire size in "short" flip chip position, in-frame storage bag
LIMITS	
MAX TIRE CLEARANCE	53mm

Precio: \$95,990.00

GEOMETRÍA

CUADRO	XS	S	M	ML
	SHORT LONG	SHORT LONG	SHORT LONG	SHORT LONG
Longitud de la Base del Poste de Asiento (mm)	430	450	470	490
Seat Post Insertion Depth (mm)	294	308	323	363
Ángulo de la Base del Poste de Asiento	74.0°	73.5°	73.5°	73.0°
Longitud del Tubo Superior (mm)	540	550	560	575
Longitud del Telescopio (mm)	125	135	150	165
Ángulo del Telescopio	70.0°	71.0°	71.5°	72.0°
Rake (mm)	50	50	50	50
Trail (mm)	78 82	72 75	68 72	65 68
Distancia entre Ejes (mm)	1024 1034	1020 1030	1026 1036	1031 1041
Longitud de Vaina Inferior (mm)	425 435	425 435	425 435	425 435
Caída del Eje de Centro (mm)	80 81	80 81	80 81	80 81
Stack (mm)	556	570	586	602
Reach (mm)	381	381	387	391
Altura del Tubo Superior al Suelo (mm)	724 731	740 747	757 764	774 780
Ancho del Manubrio (mm)	420	420	440	440
Longitud de la Potencia (mm)	50	60	70	80
Longitud de la Biela (mm)	170	170	172.5	172.5

Todas las especificaciones están sujetas a cambios sin previo aviso.