

REVOLT ADVANCED 0



TEKNISET TIEDOT

RUNKO	
KOOT	XS, S, M, M/L, L, XL
VÄRIT	Snow Drift
RUNKO	Advanced-grade composite, 12x142mm thru-axle, disc, flip chip dropout, down tube storage
HAARUKKA	Advanced-grade composite, full-composite OverDrive steerer, 12mm thru-axle, disc
KOMPONENTIT	
OHJAUSTANKO	Giant Contact XR D-Fuse, 31.8mm XS:42cm, S:42cm, M:44cm, M/L:44cm, L:46cm, XL:46cm
GRIPIT	Stratus Lite 3.0
OHJAINKANNATIN	Giant Contact AeroLight, -10 degree XS:50mm, S:60mm, M:70mm, M/L:80mm, L:80mm, XL:90mm
SATULATOLPPA	Giant D-Fuse SL, composite, -5/+15mm offset
SATULA	Giant Grit
POLKIMET	no pedal [GA, Pan-Eu], platform pedal [GU, GV, GJ]
VOIMANSIIRTO	
VAIHDEVIPU	Shimano GRX RX-820, 2x12
ETUVAIHTAJA	Shimano GRX RX-820
TAKAVAIHTAJA	Shimano GRX RX-820
JARRUT	Shimano GRX RX-820 hydraulic, Shimano SM-RT70 rotors [F]160mm, [R]160mm
JARRUKAHVAT	Shimano GRX RX-820 hydraulic
RATASPAKKA	Shimano CS-HG710, 12-speed, 11x36
KETJUT	KMC X12L-1
KAMPISARJA	Shimano GRX RX-820, 31/48 XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175mm
KESKIÖ	Shimano, press fit

RENKAAT	
VANTEET	Giant CXR 2 WheelSystem, [F] 35mm, [R] 35mm
NAVAT	[F] Giant alloy, CenterLock, 12mm thru-axle, [R] Giant alloy, 3-pawl 36t driver, CenterLock, 12mm thru-axle
PINNAT	Sapim Sprint
RENKAAT	Crosscut Grip 45c
LISÄTIEDOT	tubeless prepared, 53mm max tire size in "long" flip chip position, 45mm max tire size in "short" flip chip position, in-frame storage bag
RAJOITTEET	
MAX RENGASVARA	53mm

Suositus hinta: 4 599,00 €

GEOMETRIA

RUNKO	S	M	ML	L	XL
	SHORT LONG SHORT	LONG SHORT LONG SHORT	LONG SHORT LONG SHORT	LONG SHORT LONG SHORT	LONG SHORT LONG SHORT
Satulaputken pituus (mm)	450	470	490	510	530
Satulatolpan asennussyvyys (mm)	308	323	363	375	375
Satulaputken kulma	73,5°	73,5°	73,0°	73,0°	73,0°
Vaakaputken pituus (mm)	550	560	575	585	600
Emäputken pituus (mm)	135	150	165	180	195
Emäputken kulma	71,0°	71,5°	72,0°	72,0°	72,0°
Haarukan offset (mm)	50	50	50	50	50
Trail-mitta (mm)	72 75	68 72	65 68	65 68	65 68
Akseliväli (mm)	1020 1030	1026 1036	1031 1041	1041 1051	1056 1066
Takahaarukan alaputken pituus (mm)	425 435	425 435	425 435	425 435	425 435
Keskion pudotus (mm)	80 81	80 81	80 81	80 81	80 81
Stack-mitta (mm)	570	586	602	616	630
Reach-mitta (mm)	381	387	391	397	407
Standover-mitta (mm)	740 747	757 764	774 780	791 797	807 814
Ohjaustangon leveys (mm)	420	440	440	460	460
Ohjainkannattimen pituus (mm)	60	70	80	80	90
Kammen pituus (mm)	170	172,5	172,5	175	175

Kaikki ilmoitetut tekniset tiedot voivat muuttua ilman erillistä ilmoitusta.