

REVOLT ADVANCED 0



SPECIFICATIES

FRAME	
MATEN	XS, S, M, M/L, L, XL
KLEUREN	Charcoal Plum
FRAME	Advanced-Grade Composite, 12x142mm thru-axle, disc, flip chip dropout
VOORVORK	Advanced-Grade Composite, full-composite OverDrive steerer, 12mm thru-axle, disc
DEMPER	N/A
ONDERDELEN	
STUUR	Giant Contact XR D-Fuse, 31.8mm XS:42cm, S:42cm, M:44cm, M/L:44cm, L:46cm, XL:46cm
HANDVATTEN	Stratus Lite 3.0
STUURPEN	Giant Contact, 8-degree XS:50mm, S:60mm, M:70mm, M/L:80mm, L:80mm, XL:90mm
ZADELPEN	Giant D-Fuse, composite, 14mm offset
ZADEL	Giant Approach
PEDALEN	N/A
AFMONTAGE	
SHIFTERS	Shimano GRX RX-810, 2x11
VOORDERAILLEUR	Shimano GRX RX-810
ACHTERDERAILLEUR	Shimano GRX RX-810
REMMEN	Shimano GRX RX-810 hydraulic, Shimano SM-RT70 rotors [F]160mm, [R]160mm
REMHENDELS	Shimano GRX RX-810 hydraulic
CASSETTE	Shimano CS-HG800, 11-speed, 11x34
AANDRIJVING	KMC X11SL-1
CRANKSET	Shimano GRX RX-810, 31/48 XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175mm
BOTTOM BRACKET	Shimano, press fit

WIELSET	
VELGEN	Giant CXR 2 Carbon Disc WheelSystem, [F] 35mm, [R] 35mm
NAVEN	[F] Giant alloy, CenterLock, 12mm thru-axle, [R] Giant alloy, 3-pawl driver, CenterLock, 12mm thru-axle
SPAKEN	Sapim Sprint
BANDEN	CADEX AR, 700x40c, tubeless
EXTRA'S	tubeless prepared, 53mm max tire size in "long" flip chip position, 45mm max tire size in "short" flip chip position

Adviesprijs: € 4.299,00

GEOMETRIE

FRAME	XS	S	M	ML	L
	SHORT LONG SHORT	LONG SHORT LONG SHORT	LONG SHORT LONG SHORT	LONG SHORT LONG SHORT	LONG SHORT LONG SHORT
Zitbuis Lengte (mm)	430	450	470	490	510
Zitbuis Hoek	74,0°	73,5°	73,5°	73,0°	73,0°
Frame Lengte (horizontaal) (mm)	540	550	560	575	585
Balhoofdbuis Lengte (mm)	125	135	150	165	180
Balhoofdbuis Hoek	70,0°	71,0°	71,5°	72,0°	72,0°
Vork Sprong (mm)	50	50	50	50	50
Naloop (mm)	78 82	72 75	68 72	65 68	65 68
Wielbasis (mm)	1024 1034	1020 1030	1026 1036	1031 1041	1041 1051
Liggende achtervork lengte (mm)	425 435	425 435	425 435	425 435	425 435
Bottom Bracket Drop (mm)	80 81	80 81	80 81	80 81	80 81
Stack (mm)	556	570	586	602	616
Reach (mm)	381	381	387	391	397
Stand Over Height (mm)	724 731	740 747	757 764	774 780	791 797
Stuur breedte (mm)	420	420	440	440	460
Stuurpen Lengte (mm)	50	60	70	80	80
Cranklengte (mm)	170	170	172,5	172,5	175
Wielmaat	700C	700C	700C	700C	700C

Deze specificaties zijn met de grootste zorgvuldigheid samengesteld. Specificaties, beschikbaarheid, prijzen en kleuren kunnen echter zonder voor aankondiging wijzigen.