

REVOLT ADVANCED 0

GIANT



SPEZIFIKATIONEN

| RAHMEN       |                                                                                          |
|--------------|------------------------------------------------------------------------------------------|
| GRÖSSEN      | XS, S, M, M/L, L, XL                                                                     |
| FARBE        | Snow Drift                                                                               |
| RAHMEN       | Advanced-grade composite, 12x142mm thru-axle, disc, flip chip dropout, down tube storage |
| GABEL        | Advanced-grade composite, full-composite OverDrive steerer, 12mm thru-axle, disc         |
| KOMPONENTEN  |                                                                                          |
| LENKER       | Giant Contact XR D-Fuse, 31.8mm XS:42cm, S:42cm, M:44cm, M/L:44cm, L:46cm, XL:46cm       |
| GRIFFE       | Stratus Lite 3.0                                                                         |
| VORBAU       | Giant Contact AeroLight, -10 degree XS:50mm, S:60mm, M:70mm, M/L:80mm, L:80mm, XL:90mm   |
| SATTELSTÜTZE | Giant D-Fuse SL, composite, -5/+15mm offset                                              |
| SATTEL       | Giant Grit                                                                               |
| PEDALE       | no pedal [GA, Pan-Eu], platform pedal [GU, GV, GJ]                                       |
| ANTRIEB      |                                                                                          |
| SCHALTHEBEL  | Shimano GRX RX-820, 2x12                                                                 |
| UMWERFER     | Shimano GRX RX-820                                                                       |
| SCHALTWERK   | Shimano GRX RX-820                                                                       |
| BREMSEN      | Shimano GRX RX-820 hydraulic, Shimano SM-RT70 rotors [F]160mm, [R]160mm                  |
| BREMSHEBEL   | Shimano GRX RX-820 hydraulic                                                             |
| KASSETTE     | Shimano CS-HG710, 12-speed, 11x36                                                        |
| KETTE        | KMC X12L-1                                                                               |
| KURBEL       | Shimano GRX RX-820, 31/48 XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175mm   |
| TRETLAGER    | Shimano, press fit                                                                       |

| LAUFRÄDER          |                                                                                                                                            |
|--------------------|--------------------------------------------------------------------------------------------------------------------------------------------|
| FELGEN             | Giant CXR 2 WheelSystem, [F] 35mm, [R] 35mm                                                                                                |
| NABE               | [F] Giant alloy, CenterLock, 12mm thru-axle, [R] Giant alloy, 3-pawl 36t driver, CenterLock, 12mm thru-axle                                |
| SPEICHEN           | Sapim Sprint                                                                                                                               |
| REIFEN             | Crosscut Grip 45c                                                                                                                          |
| EXTRAS             | tubeless prepared, 53mm max tire size in "long" flip chip position, 45mm max tire size in "short" flip chip position, in-frame storage bag |
| LIMITS             |                                                                                                                                            |
| MAX TIRE CLEARANCE | 53mm                                                                                                                                       |

GEOMETRIEDATEN

| RAHMEN                         | XS           | S            | M            | ML           | L            |
|--------------------------------|--------------|--------------|--------------|--------------|--------------|
|                                | SHORT   LONG | SHORT   LONG | SHORT   LONG | SHORT   LONG | SHORT   LONG |
| Sitzrohrlänge (mm)             | 430          | 450          | 470          | 490          | 510          |
| Seat Post Insertion Depth (mm) | 294          | 308          | 323          | 363          | 375          |
| Sitzrohrwinkel                 | 74.0°        | 73.5°        | 73.5°        | 73.0°        | 73.0°        |
| Oberrohrlänge (mm)             | 540          | 550          | 560          | 575          | 585          |
| Steuerrohr-Länge (mm)          | 125          | 135          | 150          | 165          | 180          |
| Steuerrohr-Winkel              | 70.0°        | 71.0°        | 71.5°        | 72.0°        | 72.0°        |
| Gabelneigung (mm)              | 50           | 50           | 50           | 50           | 50           |
| Trail (mm)                     | 78   82      | 72   75      | 68   72      | 65   68      | 65   68      |
| Radstand (mm)                  | 1024   1034  | 1020   1030  | 1026   1036  | 1031   1041  | 1041   1051  |
| Kettenstreben-Länge (mm)       | 425   435    | 425   435    | 425   435    | 425   435    | 425   435    |
| Tretlager-Höhe (mm)            | 80   81      | 80   81      | 80   81      | 80   81      | 80   81      |
| Stack (mm)                     | 556          | 570          | 586          | 602          | 616          |
| Reach (mm)                     | 381          | 381          | 387          | 391          | 397          |
| Überstandshöhe (mm)            | 724   731    | 740   747    | 757   764    | 774   780    | 791   797    |
| Lenkerbreite (mm)              | 420          | 420          | 440          | 440          | 460          |
| Vorbaulänge (mm)               | 50           | 60           | 70           | 80           | 80           |
| Kurbellänge (mm)               | 170          | 170          | 172.5        | 172.5        | 175          |

Spezifikations-, Preis- und Farbänderungen vorbehalten.