

REVOLT ADVANCED 0



SPECIFICATIES

FRAME	
MATEN	S, M, M/L, L, XL
KLEUREN	Aurora Noise
FRAME	Advanced-grade composite, 12x142mm thru-axle, disc, flip chip dropout, down tube storage
VOORVORK	Advanced-grade composite, full-composite OverDrive steerer, 12mm thru-axle, disc
ONDERDELEN	
STUUR	Giant Contact XR D-Fuse, 31.8mm XS:42cm, S:42cm, M:44cm, M/L:44cm, L:46cm, XL:46cm
HANDVATTEN	Stratus Lite 3.0
STUURPEN	Giant Contact AeroLight, -10 degree XS:50mm, S:60mm, M:70mm, M/L:80mm, L:80mm, XL:90mm
ZADELPEN	Giant D-Fuse SL, composite, -5/+15mm offset
ZADEL	Giant Grit
AFMONTAGE	
SHIFTERS	Shimano GRX RX-820, 2x12
VOORDERAILLEUR	Shimano GRX RX-820
ACHTTERDERAILLEUR	Shimano GRX RX-820
REMMEN	Shimano GRX RX-820 hydraulic, Shimano SM-RT70 rotors [F]160mm, [R]160mm
REMHENDELS	Shimano GRX RX-820 hydraulic
CASSETTE	Shimano CS-HG710, 12-speed, 11x36
AANDRIJVING	KMC X12L-1
CRANKSET	Shimano GRX RX-820, 31/48 XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175mm
BOTTOM BRACKET	Shimano, press fit

WIELSET	
VELGEN	Giant CXR 2 Carbon Disc WheelSystem, [F] 35mm, [R] 35mm
NAVEN	[F] Giant alloy, CenterLock, 12mm thru-axle [R] Giant alloy, 3-pawl 36t driver, CenterLock, 12mm thru-axle
SPAKEN	Sapim Sprint
BANDEN	CADEX GX, 700x40c, tubeless
EXTRA'S	tubeless prepared, 53mm max tire size in "long" flip chip position, 53mm max tire size in "short" flip chip position, in-frame storage bag
LIMITS	
MAXIMALE BANDENVRIJHEID	53mm

Adviesprijs: € 4.399,00

GEOMETRIE

FRAME	S	M	ML	L	XL
	SHORT LONG	SHORT LONG	SHORT LONG	SHORT LONG	SHORT LONG
Zitbuis Lengte (mm)	450	470	490	510	530
Zitbuis Hoek	73,5°	73,5°	73,0°	73,0°	73,0°
Frame Lengte (horizontaal) (mm)	550	560	575	585	600
Balhoofdbuis Lengte (mm)	135	150	165	180	195
Balhoofdbuis Hoek	71,0°	71,5°	72,0°	72,0°	72,0°
Vork Sprong (mm)	50	50	50	50	50
Naloop (mm)	72 75	68 72	65 68	65 68	65 68
Wielbasis (mm)	1020 1030	1026 1036	1031 1041	1041 1051	1056 1066
Liggende achtersvork lengte (mm)	425 435	425 435	425 435	425 435	425 435
Bottom Bracket Drop (mm)	80 81	80 81	80 81	80 81	80 81
Stack (mm)	570	586	602	616	630
Reach (mm)	381	387	391	397	407
Stand Over Height (mm)	740 747	757 764	774 780	791 797	807 814
Stuur breedte (mm)	420	440	440	460	460
Stuurpen Lengte (mm)	60	70	80	80	90
Cranklengte (mm)	170	172,5	172,5	175	175
Wielmaat	700c	700c	700c	700c	700c

Deze specificaties zijn met de grootste zorgvuldigheid samengesteld. Specificaties, beschikbaarheid, prijzen en kleuren kunnen echter zonder vooraankondiging wijzigen.