

REVOLT ADVANCED 0 SE

GIANT



SPEZIFIKATIONEN

RAHMEN & GABEL	
RAHMENGRÖSSEN	XS, S, M, M/L, L, XL
RAHMEN	Advanced-grade composite, 12x142mm thru-axle, disc, flip chip dropout, down tube storage
GABEL	Advanced-grade composite, full-composite OverDrive steerer, 12mm thru-axle, disc
COCKPIT	
LENKER	Giant Contact XR D-Fuse, 31.8mm XS:42cm, S:42cm, M:44cm, M/L:44cm, L:46cm, XL:46cm
GRIFFE	Stratus Lite 3.0
VORBAU	Giant Contact AeroLight, -10 degree XS:50mm, S:60mm, M:70mm, M/L:80mm, L:80mm, XL:90mm
SATTELSTÜTZE	Giant D-Fuse SL, composite, -5/+15mm offset
SATTEL	Giant Grit
SCHALTUNG, ANTRIEB	
SCHALTHEBEL	Shimano GRX RX-820, 2x12
UMWERFER	Shimano GRX RX-820
SCHALTWERK	Shimano GRX RX-820
BREMSEN	Shimano GRX RX-820 hydraulic, Shimano SM-RT70 rotors [F]160mm, [R]160mm
BREMSHEBEL	Shimano GRX RX-820 hydraulic
KASSETTE	Shimano CS-HG710, 12-speed, 11x36
KETTE	KMC X12L-1
KURBELSATZ	Shimano GRX RX-820, 31/48 XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175mm
INNENLAGER	Shimano, press fit

LAUFRÄDER	
FELGEN	Giant CXR 2 WheelSystem, [F] 35mm, [R] 35mm
NABEN (V/H)	[F] Giant alloy, CenterLock, 12mm thru-axle, [R] Giant alloy, 3-pawl 36t driver, CenterLock, 12mm thru-axle
SPEICHEN	Sapim Sprint
REIFEN	CADEX GX, 700x40c, tubeless
ZUBEHÖR (TEILW. VERBAUT)	tubeless prepared, 53mm max tire size in "long" flip chip position, 45mm max tire size in "short" flip chip position, in-frame storage bag
GRENZEN	
MAX. REIFENBREITE	53mm

UVP: 4.499,00 €

GEOMETRIEDATEN

RAHMEN & GABEL	S	M	ML	L	XL
	SHORT LONG	SHORT LONG	SHORT LONG	SHORT LONG	SHORT LONG
Sitzrohlänge (mm)	450	470	490	510	530
Einstecktiefe der Sattelstütze (mm)	308	323	363	375	375
Sitzwinkel	73,5°	73,5°	73,0°	73,0°	73,0°
Oberrohrlänge (mm)	550	560	575	585	600
Steuerrohrlänge (mm)	135	150	165	180	195
Lenkwinkel	71,0°	71,5°	72,0°	72,0°	72,0°
Gabelvorbiegung (mm)	50	50	50	50	50
Gabelnachlauf (mm)	72 75	68 72	65 68	65 68	65 68
Radstand (mm)	1020 1030	1026 1036	1031 1041	1041 1051	1056 1066
Kettenstrebienlänge (mm)	425 435	425 435	425 435	425 435	425 435
Tretlagerabsenkung (mm)	80 81	80 81	80 81	80 81	80 81
Stack (mm)	570	586	602	616	630
Reach (mm)	381	387	391	397	407
Überstands-/Durchstiegshöhe (mm)	740 747	757 764	774 780	791 797	807 814
Lenkerbreite (mm)	420	440	440	460	460
Vorbaulänge (mm)	60	70	80	80	90
Kurbelarmlänge (mm)	170	172,5	172,5	175	175

Spezifikations-, Preis- und Farbänderungen vorbehalten.