

REVOLT ADVANCED 0

GIANT



ŠPECIFIKÁCIE

RÁM	
VELKOSTI	XS, S, M, M/L, L, XL
FARBY	Snow Drift
RÁM	Advanced-grade composite, 12x142mm thru-axle, disc, flip chip dropout, down tube storage
VIDLICA	Advanced-grade composite, full-composite OverDrive steerer, 12mm thru-axle, disc
KOMPONENTY	
RIADIDLÁ	Giant Contact XR D-Fuse, 31.8mm XS:42cm, S:42cm, M:44cm, M/L:44cm, L:46cm, XL:46cm
GRIPY	Stratus Lite 3.0
PREDSTAVEC	Giant Contact AeroLight, -10 degree XS:50mm, S:60mm, M:70mm, M/L:80mm, L:80mm, XL:90mm
SEDOVKA	Giant D-Fuse SL, composite, -5/+15mm offset
SEDADLO	Giant Grit
PEDÁLE	no pedal [GA, Pan-Eu], platform pedal [GU, GV, GJ]
POHON	
RADENIE	Shimano GRX RX-820, 2x12
PREŠMYKAČ	Shimano GRX RX-820
PREHADZOVAČKA	Shimano GRX RX-820
BRZDY	Shimano GRX RX-820 hydraulic, Shimano SM-RT70 rotors [F]160mm, [R]160mm
BRZDOVÉ PÁKY	Shimano GRX RX-820 hydraulic
KAZETA	Shimano CS-HG710, 12-speed, 11x36
REŤAZ	KMC X12L-1
KLUKY	Shimano GRX RX-820, 31/48 XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175mm
STREDOVÉ ZLOŽENIE	Shimano, press fit

KOLESÁ	
RÁFIKY	Giant CXR 2 WheelSystem, [F] 35mm, [R] 35mm
NÁBOJE	[F] Giant alloy, CenterLock, 12mm thru-axle, [R] Giant alloy, 3-pawl 36t driver, CenterLock, 12mm thru-axle
ŠPICE	Sapim Sprint
PNEUMATIKY	Crosscut Grip 45c
DOPLNKY	tubeless prepared, 53mm max tire size in "long" flip chip position, 45mm max tire size in "short" flip chip position, in-frame storage bag
LIMITY	
MAXIMÁLNA ŠÍRKA PNEUMATÍK	53mm

Cena: 4 399 €

GEOMETRIA

RÁM	XS	S	M	ML
	SHORT LONG	SHORT LONG	SHORT LONG	SHORT LONG
Dĺžka sedlovej trubky (mm)	430	450	470	490
Hĺbka vloženia sedlovky (mm)	294	308	323	363
Uhol sedlovej trubky	74,0°	73,5°	73,5°	73,0°
Dĺžka hornej rámovej trubky (mm)	540	550	560	575
Dĺžka hlavovej trubky (mm)	125	135	150	165
Uhol hlavovej trubky	70,0°	71,0°	71,5°	72,0°
Offset vidlice (mm)	50	50	50	50
Trail (mm)	78 82	72 75	68 72	65 68
Rázvor (mm)	1024 1034	1020 1030	1026 1036	1031 1041
Dĺžka zadnej stavby (mm)	425 435	425 435	425 435	425 435
Rozdiel zadnej voči stredovej osi - BB DROP (mm)	80 81	80 81	80 81	80 81
Stack - výška riadenia (mm)	556	570	586	602
Reach (mm)	381	381	387	391
Výška rámu od zeme (mm)	724 731	740 747	757 764	774 780
Šírka riaditok (mm)	420	420	440	440
Dĺžka predstavca (mm)	50	60	70	80
Dĺžka klúku (mm)	170	170	172,5	172,5

Všetky ceny a špecifikácie sa môžu zmeniť bez predchádzajúceho upozornenia.