



SPECIFIKACIJE

OKVIR	
VELIKOSTI	XS, S, M, M/L, L, XL
BARVE	Prismatic Haze / Aurora Noise
OKVIR	Advanced-grade composite, 12x142mm thru-axle, disc, flip chip dropout, down tube storage
VILICE	Advanced-grade composite, full-composite OverDrive steerer, 12mm thru-axle, disc
KOMPONENTE	
KRMILO	Giant Contact XR D-Fuse, 31.8mm XS:42cm, S:42cm, M:44cm, M/L:44cm, L:46cm, XL:46cm
GRIPS	Stratus Lite 3.0
OPORA KRMILA	Giant Contact AeroLight, -10 degree XS:50mm, S:60mm, M:70mm, M/L:80mm, L:80mm, XL:90mm
OPORA SEDEŽA	Giant D-Fuse SL, composite, -5/+15mm offset
SEDEŽ	Giant Grit
POGON	
PRESTAVNE ROČICE	Shimano GRX RX-820, 2x12
PREDNJI MENJALNIK	Shimano GRX RX-820
ZADNJI MENJALNIK	Shimano GRX RX-820
ZAVORE	Shimano GRX RX-820 hydraulic, Shimano SM-RT70 rotors [F]160mm, [R]160mm
ZAVORNE ROČICE	Shimano GRX RX-820 hydraulic
VERIŽNIK	Shimano CS-HG710, 12-speed, 11x36
VERIGA	KMC X12L-1
GONILKE Z VERIŽNIKI	Shimano GRX RX-820, 31/48 XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175mm
BOTTOM BRACKET	Shimano, press fit

OBROČNIKI	
OBROČI	Giant CXR 2 Carbon Disc WheelSystem, [F] 35mm, [R] 35mm
PESTA	[F] Giant alloy, CenterLock, 12mm thru-axle [R] Giant alloy, 3-pawl 36t driver, CenterLock, 12mm thru-axle
NAPERE	Sapim Sprint
PLAŠČI	CADEX GX, 700x40c, tubeless
DODATKI	tubeless prepared, 53mm max tire size in "long" flip chip position, 53mm max tire size in "short" flip chip position, in-frame storage bag
LIMITS	
MAX TIRE CLEARANCE	53mm

GEOMETRIJA

OKVIR	XS	S	M	ML	L
	SHORT LONG	SHORT LONG	SHORT LONG	SHORT LONG	SHORT LONG
Dolžina sedežne cevi (mm)	430	450	470	490	510
Kot sedežne cevi	74,0°	73,5°	73,5°	73,0°	73,0°
Top Tube Length (mm)	540	550	560	575	585
Višina glave okvirja (mm)	125	135	150	165	175
Krmlini kot	70,0°	71,0°	71,5°	72,0°	72,0°
Zamik vpetja osi (mm)	50	50	50	50	50
Trail (mm)	78 82	72 75	68 72	65 68	62 65
Medosna razdalja (mm)	1024 1034	1020 1030	1026 1036	1031 1041	1036 1046
Dolžina cevi ob verigi (mm)	425 435	425 435	425 435	425 435	425 435
Bottom Bracket Drop (mm)	80 81	80 81	80 81	80 81	80 81
Oddaljenost zgornje cevi od gonilne osi (mm)	556	570	586	602	618
Doseg (mm)	381	381	387	391	395
Višina zgornje cevi (mm)	724 731	740 747	757 764	774 780	790 797
Širina krmila (mm)	420	420	440	440	440
Dolžina opore krmila (mm)	50	60	70	80	80
Dolžina gonilke (mm)	170	170	172,5	172,5	172,5
Velikost obročnikov	700c	700c	700c	700c	700c

Vse navedene specifikacije se lahko spremenijo brez obvestila.