

REVOLT ADVANCED 0

GIANT



SPECIFIKACIJE

OKVIR	
VELIKOSTI	XS, S, M, M/L, L, XL
BARVE	Snow Drift
OKVIR	Advanced-grade composite, 12x142mm thru-axle, disc, flip chip dropout, down tube storage
VILICE	Advanced-grade composite, full-composite OverDrive steerer, 12mm thru-axle, disc
KOMPONENTE	
KRMILO	Giant Contact XR D-Fuse, 31.8mm XS:42cm, S:42cm, M:44cm, M/L:44cm, L:46cm, XL:46cm
GRIPS	Stratus Lite 3.0
OPORA KRMILA	Giant Contact AeroLight, -10 degree XS:50mm, S:60mm, M:70mm, M/L:80mm, L:80mm, XL:90mm
OPORA SEDEŽA	Giant D-Fuse SL, composite, -5/+15mm offset
SEDEŽ	Giant Grit
PEDALA	no pedal [GA, Pan-Eu], platform pedal [GU, GV, GJ]
POGON	
PRESTAVNE ROČICE	Shimano GRX RX-820, 2x12
PREDNJI MENJALNIK	Shimano GRX RX-820
ZADNJI MENJALNIK	Shimano GRX RX-820
ZAVORE	Shimano GRX RX-820 hydraulic, Shimano SM-RT70 rotors [F]160mm, [R]160mm
ZAVORNE ROČICE	Shimano GRX RX-820 hydraulic
VERIŽNIK	Shimano CS-HG710, 12-speed, 11x36
VERIGA	KMC X12L-1
GONILKE Z VERIŽNIKI	Shimano GRX RX-820, 31/48 XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175mm
BOTTOM BRACKET	Shimano, press fit

OBROČNIKI	
OBROČI	Giant CXR 2 WheelSystem, [F] 35mm, [R] 35mm
PESTA	[F] Giant alloy, CenterLock, 12mm thru-axle, [R] Giant alloy, 3-pawl 36t driver, CenterLock, 12mm thru-axle
NAPERE	Sapim Sprint
PLAŠČI	Crosscut Grip 45c
DODATKI	tubeless prepared, 53mm max tire size in "long" flip chip position, 45mm max tire size in "short" flip chip position, in-frame storage bag
LIMITS	
MAX TIRE CLEARANCE	53mm

GEOMETRIJA

OKVIR	XS	S	M	ML	
	SHORT LONG	SHORT LONG	SHORT LONG	SHORT LONG	S
Dolžina sedežne cevi (mm)	430	450	470	490	5
Seat Post Insertion Depth (mm)	294	308	323	363	3
Kot sedežne cevi	74,0°	73,5°	73,5°	73,0°	7
Top Tube Length (mm)	540	550	560	575	5
Višina glave okvirja (mm)	125	135	150	165	1
Krmilni kot	70,0°	71,0°	71,5°	72,0°	7
Zamik vpetja osi (mm)	50	50	50	50	5
Trail (mm)	78 82	72 75	68 72	65 68	6
Medosna razdalja (mm)	1024 1034	1020 1030	1026 1036	1031 1041	1
Dolžina cevi ob verigi (mm)	425 435	425 435	425 435	425 435	4
Bottom Bracket Drop (mm)	80 81	80 81	80 81	80 81	8
Oddaljenost zgornje cevi od gonilne osi (mm)	556	570	586	602	6
Doseg (mm)	381	381	387	391	3
Višina zgornje cevi (mm)	724 731	740 747	757 764	774 780	7
Širina krmila (mm)	420	420	440	440	4
Dolžina opore krmila (mm)	50	60	70	80	8
Dolžina gonilke (mm)	170	170	172,5	172,5	1

Vse navedene specifikacije se lahko spremenijo brez obvestila.