

REVOLT ADVANCED 1

GIANT



TEKNISET TIEDOT

RUNKO	
KOOT	XS, S, M, M/L, L, XL
VÄRIT	Ocean Twilight / Steampunk
RUNKO	Advanced-grade composite, 12x142mm thru-axle, disc, flip chip dropout, down tube storage
HAARUKKA	Advanced-grade composite, full-composite OverDrive steerer, 12mm thru-axle, disc
KOMONENTIT	
OHJAUSTANKO	Giant Contact XR D-Fuse, 31.8mm XS:42cm, S:42cm, M:44cm, M/L:44cm, L:46cm, XL:46cm
GRIPIT	Stratus Lite 3.0
OHJAINKANNATIN	Giant Contact AeroLight, -10 degree XS:50mm, S:60mm, M:70mm, M/L:80mm, L:80mm, XL:90mm
SATULATOLPPA	Post Moderne, dropper, 30.9mm, 30mm suspension XS:365mm, S:415mm, M:415mm, M/L:415mm, L:415mm, XL:415mm
SATULA	Giant Grit
VOIMANSIIRTO	
VAIHDEVIIPU	SRAM Apex 1, 1x12
TAKAVAIHTAJA	SRAM Apex XPLR
JARRUT	SRAM Apex hydraulic, Giant MPH rotors [F]160mm, [R]160mm
JARRUKAHVAT	SRAM Rival 1, left lever dropper switch
RATASPAKKA	SRAM PG-1231, 12-speed, 11x44
KETJUT	SRAM Apex D1
KAMPISARJA	SRAM Apex 1 Wide DUB, 40t XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175mm
KESKIÖ	SRAM DUB, press fit

RENKAAT	
VANTEET	Giant P-X2 Disc wheelset, alloy
NAVAT	Giant alloy, 12mm thru-axle
PINNAT	Sapim
RENKAAT	Giant Crosscut Grip, 700x45c, tubeless
LISÄTIEDOT	Giant 1x chain guide, tubeless prepared, 53mm max tire size in "long" flip chip position, 45mm max tire size in "short" flip chip position, in-frame storage bag
RAJOITTEET	
MAX RENGASVARA	53mm

Suositus hinta: 3 419,00 €

GEOMETRIA

RUNKO	M		ML		L	
	SHORT	LONG	SHORT	LONG	SHORT	LONG
Satulaputken pituus (mm)	470	490	490	510	510	530
Satulaputken kulma	73,5°	73,0°	73,0°	73,0°	73,0°	73,0°
Vaakaputken pituus (mm)	560	575	575	585	585	595
Emäputken pituus (mm)	150	165	165	180	180	195
Emäputken kulma	71,5°	72,0°	72,0°	72,0°	72,0°	72,0°
Haarukan offset (mm)	50	50	50	50	50	50
Trail-mitta (mm)	68 72	65 68	65 68	65 68	65 68	65 68
Akseliväli (mm)	1026 1036	1031 1041	1031 1041	1041 1051	1041 1051	1051 1061
Takahaarukan alaputken pituus (mm)	425 435	425 435	425 435	425 435	425 435	425 435
Keskiön pudotus (mm)	80 81	80 81	80 81	80 81	80 81	80 81
Stack-mitta (mm)	586	602	602	616	616	630
Reach-mitta (mm)	387	391	391	397	397	403
Standover-mitta (mm)	757 764	774 780	774 780	791 797	791 797	808 814
Ohjaustangon leveys (mm)	440	440	440	460	460	460
Ohjainkannattimen pituus (mm)	70	80	80	80	80	80
Kammen pituus (mm)	172,5	172,5	172,5	175	175	175
Rengaskoko	700c	700c	700c	700c	700c	700c

Kaikki ilmoitetut tekniset tiedot voivat muuttua ilman erillistä ilmoitusta.