

REVOLT ADVANCED 1



TECHNIQUES

CADRE	
TAILLES	XS, S, M, ML, L, XL
COLORIS	Abyss Teal
CADRE	Advanced-grade composite, 12x142mm thru-axle, disc, flip chip dropout, down tube storage
FOURCHE	Advanced-grade composite, full-composite OverDrive steerer, 12mm thru-axle, disc
COMPOSANTS	
CINTRE	Giant Contact XR D-Fuse, 31.8mm XS:42cm, S:42cm, M:44cm, M/L:44cm, L:46cm, XL:46cm
POIGNÉES	Stratus Lite 3.0
POTENCE	Giant Contact AeroLight, -10 degree XS:50mm, S:60mm, M:70mm, M/L:80mm, L:80mm, XL:90mm
TIGE DE SELLE	Giant D-Fuse, composite, 14mm offset
SELLE	Giant Grit
DÉRAILLEUR	
MANETTES	SRAM AXS Apex, 1x12
DÉRAILLEUR ARRIÈRE	SRAM Apex XPLR
FREINS	SRAM Apex hydraulic, Giant MPH rotors [F]160mm, [R]160mm
LEVIER DE FREIN	SRAM Apex D1, left lever dropper switch
CASSETTE	SRAM PG-1231, 12-speed, 11x44
CHAÎNE	SRAM Apex D1
PÉDALIER	SRAM Apex 1 Wide DUB, 38t XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175mm
BOITIER DE PÉDALIER	SRAM DUB, press fit

ROUES	
JANTES	Giant P-X2, alloy
MOYEUX	Giant alloy, 12mm thru-axle
RAYONS	Sapim
PNEUS	Giant Crosscut Grip 1, 700x45c, tubeless
EXTRAS	tubeless prepared, in-frame storage bag
LIMITES	
DÉGAGEMENT MAX DES PNEUS	53mm max tire size in "long" flip chip position, 45mm max tire size in "short" flip chip position

Prix Public Conseillé: 3 500,00 €

GÉOMÉTRIE

CADRE	XS	S	M	ML	L
	SHORT LONG	SHORT LONG	SHORT LONG	SHORT LONG	SHORT LONG
Longueur de tube de selle (mm)	430	450	470	490	510
Seat Post Insertion Depth (mm)	294	308	323	363	375
Angle de tube de selle	74,0°	73,5°	73,5°	73,0°	73,0°
Longueur du tube supérieur (mm)	540	550	560	575	585
Longueur du tube de direction (mm)	125	135	150	165	180
Angle du tube de direction	70,0°	71,0°	71,5°	72,0°	72,0°
Déport de fourche (mm)	50	50	50	50	50
Trail (mm)	78 82	72 75	68 72	65 68	65 68
Empattement (mm)	1024 1034	1020 1030	1026 1036	1031 1041	1041 10
Longueur des bases (mm)	425 435	425 435	425 435	425 435	425 435
Drop du boîtier de pédalier (mm)	80 81	80 81	80 81	80 81	80 81
Stack (mm)	556	570	586	602	616
Reach (mm)	381	381	387	391	397
Hauteur en statique (mm)	724 731	740 747	757 764	774 780	791 797
Largeur de cintre (mm)	420	420	440	440	460
Longueur de potence (mm)	50	60	70	80	80
Longueur des manivelles (mm)	170	170	172,5	172,5	175

Produits conformes aux exigences de sécurité (décret n° 2016-364 du 29 mars 2016).
GIANT France se réserve le droit de modifier les spécifications sans préavis.