

# REVOLT ADVANCED 1



## SPECIFICATIES

FRAME	
MATEN	S, M, M/L, L, XL
KLEUREN	Ocean Twilight
FRAME	Advanced-grade composite, 12x142mm thru-axle, disc, flip chip dropout, down tube storage
VOORVORK	Advanced-grade composite, full-composite OverDrive steerer, 12mm thru-axle, disc
ONDERDELEN	
STUUR	Giant Contact XR D-Fuse, 31.8mm XS:42cm, S:42cm, M:44cm, M/L:44cm, L:46cm, XL:46cm
HANDVATTEN	Stratus Lite 3.0
STUURPEN	Giant Contact AeroLight, -10 degree XS:50mm, S:60mm, M:70mm, M/L:80mm, L:80mm, XL:90mm
ZADELPEEN	Post Moderne, dropper, 30.9mm, 30mm suspension XS:365mm, S:415mm, M:415mm, M/L:415mm, L:415mm, XL:415mm
ZADEL	Giant Grit
AFMONTAGE	
SHIFTERS	SRAM Apex 1, 1x12
ACHTERDERAILLEUR	SRAM Apex XPLR
REMMEN	SRAM Apex hydraulic, Giant MPH rotors [F]160mm, [R]160mm
REMHENDELS	SRAM Rival 1, left lever dropper switch
CASSETTE	SRAM PG-1231, 12-speed, 11x44
AANDRIJVING	SRAM Apex D1
CRANKSET	SRAM Apex 1 Wide DUB, 40t XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175mm
BOTTOM BRACKET	SRAM DUB, press fit

WIELSET	
VELGEN	Giant P-X2 Disc wheelset, alloy
NAVEN	Giant alloy, 12mm thru-axle
SPAKEN	Sapim
BANDEN	Giant Crosscut Grip, 700x45c, tubeless
EXTRA'S	Giant 1x chain guide, tubeless prepared, 53mm max tire size in "long" flip chip position, 45mm max tire size in "short" flip chip position, in-frame storage bag
LIMITS	
MAX TIRE CLEARANCE	53mm

Adviesprijs: € 3.299,00

## GEOMETRIE

FRAME	S		M		ML		L		XL	
	SHORT	LONG SHORT	LONG SHORT	LONG SHORT	LONG SHORT	LONG SHORT	LONG SHORT	LONG SHORT	LONG SHORT	LONG
Zitbuis lengte (mm)	450	470	490	510	530					
Zitbuis hoek	73,5°	73,5°	73,0°	73,0°	73,0°					
Frame Lengte (horizontaal) (mm)	550	560	575	585	600					
Balhoofdbuis Lengte (mm)	135	150	165	180	195					
Balhoofdbuis Hoek	71,0°	71,5°	72,0°	72,0°	72,0°					
Vork Sprong (mm)	50	50	50	50	50					
Naloop (mm)	72   75	68   72	65   68	65   68	65   68					
Wielbasis (mm)	1020   1030	1026   1036	1031   1041	1041   1051	1056   1066					
Liggende achtervork lengte (mm)	425   435	425   435	425   435	425   435	425   435					
Bottom Bracket Drop (mm)	80   81	80   81	80   81	80   81	80   81					
Stack (mm)	570	586	602	616	630					
Reach (mm)	381	387	391	397	407					
Stand Over Height (mm)	740   747	757   764	774   780	791   797	807   814					
Stuur breedte (mm)	420	440	440	460	460					
Stuurpen Lengte (mm)	60	70	80	80	90					
Cranklengte (mm)	170	172,5	172,5	175	175					
Wielmaat	700c	700c	700c	700c	700c					

Deze specificaties zijn met de grootste zorgvuldigheid samengesteld. Specificaties, beschikbaarheid, prijzen en kleuren kunnen echter zonder voorafkondiging wijzigen.