

REVOLT ADVANCED 1



SPECS

RAMME	
STØRRELSE	XS, S, M, M/L, L, XL
FARGE	Midnight Moon
RAMME	Advanced-grade composite, 12x142mm thru-axle, disc, flip chip dropout, down tube storage
GAFFEL	Advanced-grade composite, full-composite OverDrive steerer, 12mm thru-axle, disc
KOMPONENTER	
STYRE	Giant Contact XR D-Fuse, 31.8mm XS:42cm, S:42cm, M:44cm, M/L:44cm, L:46cm, XL:46cm
GRIPS	Stratus Lite 3.0
STYRSTEM	Giant Contact AeroLight, -10 degree XS:50mm, S:60mm, M:70mm, M/L:80mm, L:80mm, XL:90mm
SETEPINNE	Post Moderne, dropper, 30.9mm, 30mm suspension XS:295mm, S:345mm, M:345mm, M/L:345mm, L:395mm, XL:395mm
SADEL	Giant Grit
DRIVVERK	
GIRHENDLER	SRAM Apex 1, 1x12
FRONTGIR	N/A
BAKGIR	SRAM Apex XPLR
BREMSE	SRAM Apex hydraulic, Giant MPH rotors [F]160mm, [R]160mm
BREMSEHENDLER	SRAM Apex 1, left lever dropper switch
KASSETT	SRAM PG-1231, 12-speed, 11x44
KJEDE	SRAM Apex D1
KRANK	SRAM Apex 1 Wide DUB, 40t XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175mm
BOTTOM BRACKET	SRAM DUB, press fit

HJUL	
FELG	Giant P-X2, alloy
NAV	Giant alloy, 12mm thru-axle
EIKE	Sapim
DEKK	Crosscut Grip 45c
EXTRAS	Giant 1x chain guide, tubeless prepared, 53mm max tire size in "long" flip chip position, 45mm max tire size in "short" flip chip position, in-frame storage bag
LIMITS	
MAX TIRE CLEARANCE	53mm

GEOMETRI

RAMME	XS	S	M	ML	L
	SHORT LONG	SHORT LONG	SHORT LONG	SHORT LONG	SHORT LONG
Seat Tube Length (mm)	430	450	470	490	510
Seat Post Insertion Depth (mm)	294	308	323	363	375
Seat Tube Angle	74,0°	73,5°	73,5°	73,0°	73,0°
Top Tube Length (mm)	540	550	560	575	585
Head Tube Length (mm)	125	135	150	165	180
Head Tube Angle	70,0°	71,0°	71,5°	72,0°	72,0°
Fork Rake (mm)	50	50	50	50	50
Trail (mm)	78 82	72 75	68 72	65 68	65 68
Wheelbase (mm)	1024 1034	1020 1030	1026 1036	1031 1041	1041 1051
Chain Stay Length (mm)	425 435	425 435	425 435	425 435	425 435
Bottom Bracket Drop (mm)	80 81	80 81	80 81	80 81	80 81
Stack (mm)	556	570	586	602	616
Reach (mm)	381	381	387	391	397
Stand Over Height (mm)	724 731	740 747	757 764	774 780	791 797
Handlebar Width (mm)	420	420	440	440	460
Stem Length (mm)	50	60	70	80	80
Crank Length (mm)	170	170	172,5	172,5	175

Alle spesifikasjonene kan endres uten varsel.