

REVOLT ADVANCED 1



SPECIFIKACIJE

OKVIR	
VELIKOSTI	XS, S, M, M/L, L, XL
BARVE	Midnight Moon
OKVIR	Advanced-grade composite, 12x142mm thru-axle, disc, flip chip dropout, down tube storage
VILICE	Advanced-grade composite, full-composite OverDrive steerer, 12mm thru-axle, disc
KOMPONENTE	
KRMILO	Giant Contact XR D-Fuse, 31.8mm XS:42cm, S:42cm, M:44cm, M/L:44cm, L:46cm, XL:46cm
GRIPS	Stratus Lite 3.0
OPORA KRMILA	Giant Contact AeroLight, -10 degree XS:50mm, S:60mm, M:70mm, M/L:80mm, L:80mm, XL:90mm
OPORA SEDEŽA	Post Moderne, dropper, 30.9mm, 30mm suspension XS:295mm, S:345mm, M:345mm, M/L:345mm, L:395mm, XL:395mm
SEDEŽ	Giant Grit
POGON	
PRESTAVNE ROČICE	SRAM Apex 1, 1x12
PREDNJI MENJALNIK	N/A
ZADNJI MENJALNIK	SRAM Apex XPLR
ZAVORE	SRAM Apex hydraulic, Giant MPH rotors [F]160mm, [R]160mm
ZAVORNE ROČICE	SRAM Apex 1, left lever dropper switch
VERIŽNIK	SRAM PG-1231, 12-speed, 11x44
VERIGA	SRAM Apex D1
GONILKE Z VERIŽNIKI	SRAM Apex 1 Wide DUB, 40t XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175mm
BOTTOM BRACKET	SRAM DUB, press fit

OBROČNIKI	
OBROČI	Giant P-X2, alloy
PESTA	Giant alloy, 12mm thru-axle
NAPERE	Sapim
PLAŠČI	Crosscut Grip 45c
DODATKI	Giant 1x chain guide, tubeless prepared, 53mm max tire size in "long" flip chip position, 45mm max tire size in "short" flip chip position, in-frame storage bag
LIMITS	
MAX TIRE CLEARANCE	53mm

GEOMETRIJA

OKVIR	XS	S	M	ML	
	SHORT LONG	SHORT LONG	SHORT LONG	SHORT LONG	S
Dolžina sedežne cevi (mm)	430	450	470	490	5
Seat Post Insertion Depth (mm)	294	308	323	363	3
Kot sedežne cevi	74,0°	73,5°	73,5°	73,0°	7
Top Tube Length (mm)	540	550	560	575	5
Višina glave okvirja (mm)	125	135	150	165	1
Krmilni kot	70,0°	71,0°	71,5°	72,0°	7
Zamik vpetja osi (mm)	50	50	50	50	5
Trail (mm)	78 82	72 75	68 72	65 68	6
Medosna razdalja (mm)	1024 1034	1020 1030	1026 1036	1031 1041	1
Dolžina cevi ob verigi (mm)	425 435	425 435	425 435	425 435	4
Bottom Bracket Drop (mm)	80 81	80 81	80 81	80 81	8
Oddaljenost zgornje cevi od gonilne osi (mm)	556	570	586	602	6
Doseg (mm)	381	381	387	391	3
Višina zgornje cevi (mm)	724 731	740 747	757 764	774 780	7
Širina krmila (mm)	420	420	440	440	4
Dolžina opore krmila (mm)	50	60	70	80	8
Dolžina gonilke (mm)	170	170	172,5	172,5	1

Vse navedene specifikacije se lahko spremenijo brez obvestila.